

## Release Notes – MC67NA WM - BSP v03.46.39 – Hotfix CFE v01.01.02 Package

- [Introduction](#)
- [Description](#)
- [Package Details](#)
- [Device Compatibility](#)
- [Installation Requirements](#)
- [Installation Instructions](#)
- [Release Date](#)

### Introduction

HotFix CFE (Cumulative Fixes from Engineering) Package includes multiple SPR Hotfixes contained into a single package. The HotFix CFE Package helps the end users to keep up to date with all the SPR hotfixes for given product software release / revision.

HotFix CFE packages are validated only by engineering validation team and the package follows Zebra Technologies HotFix Package Policy. Click here to view HotFix Package Policy. [HotFix Support Policy.doc](#)

### Description

The content and related Hotfixes that are included in this HotFix CFE\_MC67\_NA\_034639\_WM\_EN\_v010102\_e.cab is as follows.

SPR No	Synopsis
26449	MC67 GPS accuracy issue

### Package Details

CFE\_MC67\_NA\_034639\_WM\_EN\_v010102\_e.cab (CFE package without Warm boot)

### Device Compatibility

This HotFix CFE Package software release has been approved for use with the following Zebra devices.

Device	Operating System	BSP Version
MC67NA	WEHH (6.5)	v03.46.39

### Installation Requirements

The HotFix CFE cab can be deployed to the Mobile device through any one of the below mentioned methods. For installing the cab, the users should have at least one of the below mentioned tools.

- Windows Mobile Device Centre (For Windows Desktops)
- SD Cards / Micro SD cards

### Installation Instructions

- Windows Mobile Device Centre (For Windows Desktops) Installation Instructions:**
  - Copy “CFE\_MC67\_NA\_034639\_WM\_EN\_v010102\_e.cab” file to the Application folder on the device.
  - Deploy the solution by tapping on the “CFE\_MC67\_NA\_034639\_WM\_EN\_v010102\_e.cab” file.
  - Change will take effect after manual reboot of the terminal is done.
- SD Cards / Micro SD cards Installation Instructions:**
  - Copy “CFE\_MC67\_NA\_034639\_WM\_EN\_v010102\_e.cab” file to the SD card.
  - Deploy the solution by tapping on the “CFE\_MC67\_NA\_034639\_WM\_EN\_v010102\_e.cab”.
  - Change will take effect after manual reboot of the terminal is done.

### Release Date

December 2014