



**ZEBRA**

# 8000T Wet Tack

## FEATURES

- Thermal transfer, gloss polypropylene label with a permanent rubber adhesive
- Performs well in normal to freezer temperatures
- Recommended for use in cold, damp environments on rigid containers
- Adhesive meets FDA 175.105 for indirect food contact
- Available in white (10027353RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	Gloss white polypropylene film	2.6 mil
Adhesive	All-Temp permanent, rubber-based	0.7 mil
Liner	40 lb. semi-bleached, kraft stock	2.4 mil
<b>TOTAL ± 10%</b>		<b>5.7 mil</b>

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
-10° F (-23° C)	-65° F to 150° F (-54° C to 66° C)	72° F (22° C) at 50% RH

### Expected Exterior Life

1 year

## CHEMICAL RESISTANCE

Chemical		Suggested Ribbon
		6200
Weak	Blood	●
	Body Fluid	●
	Salt Water	●
	Water	●
	Window Cleaner	●
Moderate	Alcohol	●
	Ammonia	●
	Bleach	●
	IPA	●
Harsh	Gasoline	●
	Grease	●
	Oil	●
Extreme	Acetone	●
	IR Reflow	●
	MEK	●
	TCE	●
	Xylene	●

● Recommended ● Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

- Food labeling



For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | [inquiry4@zebra.com](mailto:inquiry4@zebra.com)

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. 01/2018