



# Device Central 3.2

## Release Notes – July 2021

### Highlights

- **Android 11 support** - Device Central now supports Zebra devices running Android 11
- **Support terminated for Android 8.1 Oreo** – Device Central 3.1 was the final version to support devices running Android 8.1 Oreo

### Device Support

- **Newly added device support in this release:** ET51, MC20, MC33ax, and TC52ax running Android 11

See [all supported devices](#)

### New in Device Central 3.2

- None

### Resolved Issues

- When using the **Scan to Pair** option with a Bluetooth printer, the resulting Bluetooth connection now displays the correct printer icon.

### Usage Notes

- When in Android Multi-user mode, Device Central supports only the Primary user.
- The scanning profile named “DeviceCentral” in DataWedge is used by Device Central and should not be removed or modified. Otherwise, unexpected behavior may occur.
- Only Zebra Bluetooth scanners are listed in the notification drawer in Android. All other devices are listed only in the Device Central main UI.
- The Device Central application must be installed on the device before being configured with Device Central Manager CSP.
- The Device Central application must be installed and launched at least once on the device to receive Smart Leash alerts.
- The serial number for HS3100 Bluetooth headset may report incorrectly.
- When connecting the RS6000 scanner, HS3100 headset or another Bluetooth peripheral device that provides battery information, it may take 10-15 seconds for the battery information to appear.

### Known Issues

- When scanning a BT peripheral MAC address barcode, a message sometimes appears prompting to try again, even though the barcode scanned successfully.



- After an Enterprise Reset, or a device reboot, the user would be required to switch off and switch on the Smart Leash option, in order to use the Smart Leash functionalities.

## Important Links

- [About Device Central](#)
- [Using Device Central](#)

## About Device Central

Device Central provides a centralized way for an organization to connect and monitor supported Bluetooth peripherals. Using the simple user interface, Device Central easily pairs and unpairs Bluetooth peripherals, monitors connection status, and provides details on supported peripherals. If supported by the peripheral, additional capabilities may exist such as paging the peripheral or updating the firmware.