



# ES400 OPERATING SYSTEM BSP V04.47.0002 HOTFIX CFE V1.0 RELEASE NOTES

## INTRODUCTION

SPR 27814, SMS ringtone gets set to low volume, when device moves from poor or no network coverage area to good quality network coverage area.

## DESCRIPTION

The provided cab file resolves the issue that SMS ringtone gets set to low volume, when device moves from poor or no network coverage area to good quality network coverage area.

## CONTENTS

SPR27814\_ES400\_W65\_en\_044702\_v1\_0\_WB.cab  
SPR27814\_ES400\_W65\_en\_044702\_v1\_0\_NB.cab

## DEVICE COMPATIBILITY

This software release has been approved for use with the following Zebra devices.

Device	Operating System
ES400	Windows Mobile 6.5

## INSTALLATION REQUIREMENTS

Device	OEM Version
ES400	BSP 04.47.02

## INSTALLATION INSTRUCTIONS

For NORMAL installation of the PATCH:

1. Copy “SPR27814\_ES400\_W65\_en\_044702\_v1\_0\_WB.cab” file to the device.
2. Deploy the solution by tapping on the “SPR27814\_ES400\_W65\_en\_044702\_v1\_0\_WB.cab” file.



3. After successful deployment of the “SPR27814\_ES400\_W65\_en\_044702\_v1\_0\_WB.cab” file, device will do an automatic warm boot.

For MSP or REMOTE installation of the PATCH, use SPR27814\_ES400\_W65\_en\_044702\_v1\_0\_NB.cab. This cab will not perform an automatic warm boot.

MSP/Remote Installer is responsible for performing the warm boot.

## PART NUMBER AND RELEASE DATE

December 2015