



# TC55 RESET PACKAGE FOR GSM NON-GMS DEVICES BSP 01.45.00 RELEASE NOTES

## INTRODUCTION

These packages will put the terminal into default factory settings

## DESCRIPTION

- The T55N0JB0VAFEN14500.apf contains MSP deployment package to perform factory reset on the terminal.
- The T55N0JB0VAEEN14500.apf contains MSP deployment package to perform factory reset on the terminal and it will not erase the Enterprise folder.

## CONTENTS

1. T55N0JB0VAEEN14500.apf– A MSP Enterprise Reset update package
2. T55N0JB0VAFEN14500.apf– A MSP Factory Reset update package

## DEVICE COMPATIBILITY

This software release has been approved for use with the following devices.

Device Part Number	Operating System
TC55	JellyBean 4.1.2

## INSTALLATION REQUIREMENTS

- TC55 device must be running with Android JellyBean operating system
- Mobility Service Platform

## INSTALLATION INSTRUCTIONS

Please refer Mobility Service Platform deployment guide for instruction.

2. Upload MSP package to the MSP server
3. Connect the device to Wi-Fi network which is connected to MSP server.
4. On the device launch the MSP Rapid Deployment App located in the Apps section.
5. Click on Scan Barcodes and scan barcodes



## PART NUMBER AND RELEASE DATE

T55N0JB0VAEEN14500

T55N0JB0VAFEN14500

October 20, 2013