

Zebra Robotics Automation™

Zebra Research

Advance Autonomous Mobile Development with the Zebra Research. Zebra's fully autonomous Zebra Research base is a safe and cost-effective solution to accelerate the development of automated products and solutions for a wide range of applications.



Zebra Research: The Original AMR Platform

With their highly extensible hardware design, Zebra Research autonomous mobile bases have become great enablers for researchers and corporate innovation centers looking to develop mobile robotic technologies.

Features

- Mobility to traverse ADA-compliant buildings. Specific attention was paid to the door threshold, elevator gap, and ramp requirements.
- A sensor suite suitable for the perception of objects, navigation, and manipulation in dynamic environments.
- Sufficient battery power to work an 8-hour day and an available charge dock for autonomous charging.
- Collaborative fully autonomous mobile robot base and modular top plate with 73-threaded mount points.
- Auxiliary access via top surface to 2 power ports, direct communication bus, Ethernet, and USB 3.0 ports. Side interface panel with Ethernet, USB 3.0, and DisplayPort.
- Built to work with the Robot Operating System (ROS). By using a standard software platform, many developers are already familiar with the tool set and can quickly start working with the robot.
- All the applications shipped on the Zebra Research except for firmware and some low-level drivers, are open sourced under permissive licenses. This allows developers to continue improving the autonomous capabilities of the robot and sharing of their contributions with the developing community.



AMR Base for Research: Meet the Platform

The Zebra Research base provides a common robotics platform for researchers around the world to collaborate and share research. The research platform was designed to work with the Robot Operating Systems (ROS) for the greatest common usability and familiarity.



Zebra Research Specifications

Weight	68 kg (150 lbs)
Height	359 mm (14 in.)
Base Footprint	508 mm (20 in.) wide; 559 mm (22 in.) diameter
Payload	100 kg (220 lbs)
Max Speed	1.75 m/s
Turning Radius	Turn in place
Battery	Deka 8G22NF Sealed Lead Acid
Nominal Continuous Runtime	9 hours
Charging	Autonomous docking
Charge Time	3 hours to 90%
2D Laser Sensor	SICK TiM 571, 25 m, 220°
Processor	Intel Core i7-9700E
RAM	32GB
Hard Drive	256GB SSD
Wireless	Intel AX200 802.11.ax and Bluetooth® 5.1
Side Interface Panel	DisplayPort, 2x USB 3.0, Ethernet
Audio	4x Speakers, 10W per channel
Environment	Indoor
Traversable Aisle	95 cm (37.4 in.)
Traversable Gap	15 mm (0.59 in.)
Torque for M5 Mounting Points	3.6 N-m (31.9 in.-lb.)
Installed Software	Ubuntu Linux® LTS, ROS
Installed Applications	ROS Navigation, joystick teleop, calibration



WARNING: This product uses components which emit invisible laser radiation. Incorrect use or observing the safety laser scanner through optical instruments (such as magnifying glasses, lenses, telescopes) may be hazardous for the eyes.



Zebra AMRs carry a CE mark and meet regulatory requirements for product safety.

ANSI/RIA R15.08

Zebra AMRs conform with R15.08 safety standards published by the RIA (Robotics Industry Association)

For more information about Zebra's autonomous mobile robot solutions,
please visit zebra.com/automation-solutions



NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

EMEA Headquarters | zebra.com/locations | contact.emea@zebra.com

ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. ©2024 Zebra Technologies Corp. and/or its affiliates. 11/14/2024