

IQ Color 2000D 7 mil Tag

ZEBRA

FEATURES

- · Direct thermal, smooth 7 mil paper tag
- Ability to print vibrant color on demand in predefined zones to be used as a visual cue
- Offers flexibility over traditional pre-printed labels. requiring fewer roll changes for customers using multiple SKUs
- · Limited resistance to moisture and abrasion
- Choose from 8 standard direct thermal colors -Magenta, Red, Orange, Yellow, Green, Cyan, Blue and Purple (10024694RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth topcoated paper	7.0 mil
	TOTAL ± 10%	7.0 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
N/A	-40° F to 120° F (-40° C to 49° C)	6 mos when stored at 72° F (22° C) at 50% RH

EXPECTED EXTERIOR LIFE

Not recommended for outdoor use

CHEMICAL RESISTANCE

	Chemical		Direct Thermal
	Weak	Blood	NR
		Body Fluid	NR
		Salt Water	NR
		Water	NR
		Window Cleaner	NR
	Moderate	Alcohol	NR
		Ammonia	NR
		Bleach	NR
		IPA	NR
	Harsh	Gasoline	NR
		Grease	NR
		Oil	NR
	Extreme	Acetone	NR
		IR Reflow	NR
		MEK	NR
		TCE	NR
		Xylene	NR



SUGGESTED APPLICATIONS

Ticketing



Work in process



Retail hang tags

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com



IQ Color 2000D 7 mil Tag

LIFESPAN OF IQ COLOR INKS

IQ Color Ink	Lifespan (months) for typical office and warehouse conditions (direct lighting)	Lifespan (months) for typical office <u>filing</u> conditions (no light exposure)
Yellow	1	12
Green	1	12
Red	3	12
Orange	3	12
Cyan	6	12
Magenta	6	12
Blue	6	12
Purple	6	12
Black	6	12

RECOMMENDED PRINT SPEEDS

Normal (picket-fence) codes -- 6 ips maximum Rotated (ladder) codes -- 3 ips maximum

BAR CODE DENSITY

Minimum 10 mil narrow bar normal codes (2 dot code at 203 dpi)

Minimum 15 mil narrow bar rotated codes (3 dot code at 203 dpi)

PRINTHEAD CLEANING

Zebra recommends cleaning with an alcohol swab after each roll of media is printed.

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.