

6200 Standard Resin Ribbon

Resin ribbon providing outstanding print quality, resistant to most harsh environments

A standard resin ribbon formulation that produces images resistant to most harsh environments including smearing, moisture, abrasion, extreme temperature and chemicals, when printed on Zebra's gloss paper and gloss synthetic label and tag materials.



Suggested Applications

- · Labels which are repeatedly wand-scanned
- Shelf and scan-pallet labels
- · Labels subject to abrasion or friction
- · Outdoor labeling applications in extreme environments
- Chemical drum labeling applications
- · Labels exposed to water, steam, alkali or acid solutions

Specifications

Attributes	
Color	Black
Ink Formulation	Resin
Base Film	Polyester
Base Film Caliper	4.5 microns
Total Caliper	6.9 microns +/- 10%
Scanning Capabilities	IR and Visible Light

Regulatory Compliance

Z-Supreme 2000T - UL Recognized

Z-Supreme 4000T - UL Recognized

Z-Ultimate® 4000T White & Silver - UL Recognized

Z-Ultimate® 2000T White - UL Recognized

Z-Xtreme 4000T White & Silver - UL Recognized

Z-Xtreme 4000T High-Tack White & Silver - UL Recognized Z-Xtreme 2000T White, Silver & Clear - UL Recognized

Product Performance and Suitability

1 Todact 1 Criofinance and Saltability	
Recommended storage conditions	72° F (22° C) at 50% RH
Expected Shelf Life	1 Year

6200 Standard Resin Ribbon - UL certified ribbon, with outstanding print quality, resistant to most harsh environments. For more information, please visit www.zebra.com/supplies

