# Apr.

### **ZEBRA**

## 8000D High-Temp


#### **FEATURES**

- Direct thermal paper label with an all-temp permanent acrylic adhesive
- Excellent print quality
- Provides temperature resistance up to 194° F
- Has 12x the life of conventional direct thermal products under fluorescent bulbs and partial UV exposure (through a window)
- · Meets FDA 175.105 for indirect food contact
- Available in white (66037RM)

#### **MATERIAL CONSTRUCTION**

| Component | Description                       | Caliper |
|-----------|-----------------------------------|---------|
| Facestock | White woven nylon                 | 3.2 mil |
| Adhesive  | All-temp, acrylic-based           | 0.8 mil |
| Liner     | 40 lb. semi-bleached, kraft stock |         |
|           | TOTAL ± 10%                       | 6.3 mil |

#### **ADHESIVE STRENGTH**



#### **TEMPERATURE PERFORMANCE**

| Minimum<br>Application<br>Temperature | Service<br>Temperature                | Optimal<br>Storage<br>Conditions |
|---------------------------------------|---------------------------------------|----------------------------------|
| -40° F (-40° C)                       | -40° F to 194° F<br>(-40° C to 90° C) | 72° F (22° C)<br>at 50% RH       |

## **Expected Exterior Life**Minimal outdoor life

#### **CHEMICAL RESISTANCE**

|          | Chemical       | Suggested Ribbon |
|----------|----------------|------------------|
| Weak     | Blood          | •                |
|          | Body Fluid     | •                |
|          | Salt Water     | •                |
|          | Water          | •                |
|          | Window Cleaner | •                |
| Moderate | Alcohol        | NR               |
|          | Ammonia        | NR               |
|          | Bleach         | NR               |
|          | IPA            | NR               |
| Harsh    | Gasoline       | NR               |
|          | Grease         | NR               |
|          | Oil            | NR               |
| Extreme  | Acetone        | NR               |
|          | IR Reflow      | NR               |
|          | MEK            | NR               |
|          | TCE            | NR               |
|          | Xylene         | NR               |

Recommended
Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

#### For more information, visit www.zebra.com/supplies

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.

## SUGGESTED APPLICATIONS

Hot food labeling (Pizza, Coffee, etc.)



Archival use

