

ZEBRA

8000D Linerless

FEATURES

- Direct thermal, linerless, paper label with a permanent acrylic adhesive
- Excellent print quality
- Good scratch/smear resistance
- · Not to be used in applications using chemicals
- Excellent print quality when used in linerless printer.
- · No liner allows more labels per roll and no waste
- Available in white (05987RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth direct thermal silicone coated paper	3.2 mil
Adhesive	Permanent, acrylic- based	0.8 mil
	TOTAL ± 10%	4.2 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
40° F (4° C)	-40° F to 140° F (-40° C to 60° C)	72° F (22° C) at 50% RH

Expected Exterior Life

Not recommended for outdoor use

CHEMICAL RESISTANCE

Cl	nemical	Direct Thermal
Weak	Blood	
	Body Fluid	
	Salt Water	
	Water	
	Window Cleaner	
Moderate	Alcohol	NR
	Ammonia	NR
	Bleach	NR
	IPA	NR
Harsh	Gasoline	NR
	Grease	NR
	Oil	NR
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

■ Recommended
● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

Mobile point of sale labeling



Work in process labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies