

ZEBRA

8000D Shelf Label


FEATURES

- Direct thermal, matte polypropylene label with an all-temp acrylic adhesive that will withstand refrigeration and freezers.
- Good smear/scratch resistance
- Recommended for use with 8000D Shelf Talker Clear
- Available in white (05285RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White matte topcoated polypropylene	3.2 mil
Adhesive	High Performance, acrylic-based	0.7 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
	TOTAL ± 10%	6.4 mil

ADHESIVE STRENGTH



TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
-20º F (-29º C)	-40° F to 150° F (-40° C to 66° C)	72° F (22° C) at 50% RH

Expected Exterior Life

Not recommended for outdoor use

CHEMICAL RESISTANCE

	Chemical	Direct Thermal
Weak	Blood	•
	Body Fluid	•
	Salt Water	•
	Water	•
	Window Cleaner	•
Moderate	Alcohol	NR
	Ammonia	NR
	Bleach	NR
	IPA	NR
Harsh	Gasoline	NR
	Grease	NR
	Oil	NR
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

Recommended ○ Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

Shelf labeling



· Cold storage labeling



 Labeling of most packaging materials and plastic substrates



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies