

8000D Wet Tack

FEATURES

- Direct thermal, matte polypropylene label with a permanent rubber adhesive
- Excellent adhesion to wet surfaces
- Good environmental resistance
- Performs well in normal to freezer temperatures
- Recommended for use in cold, damp environments on rigid containers
- Adhesive meets FDA 175.105 for indirect food contact
- Available in white (10026506RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	Matte white polypropylene film	4.2 mil
Adhesive	All-Temp permanent, rubber-based	1.0 mil
Liner	40 lb. semi-bleached, kraft stock	2.4 mil
	TOTAL ± 10%	7.6 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
-10° F (-23° C)	-65° F to 150° F (-54° C to 66° C)	72° F (22° C) at 50% RH

Expected Exterior Life

1 year

CHEMICAL RESISTANCE

Chemical		Direct Thermal
Weak	Blood	•
	Body Fluid	•
	Salt Water	•
	Water	•
	Window Cleaner	•
_	Alcohol	•
Moderate	Ammonia	•
Mod	Bleach	•
	IPA	•
Harsh	Gasoline	•
	Grease	•
	Oil	•
Extreme	Acetone	•
	IR Reflow	•
	MEK	•
	TCE	•
	Xylene	•

Recommended
Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

Food labeling



For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.