

ZEBRA

8000T Checkerboard Gloss

FEATURES

- Thermal transfer, silver, gloss polyester label with a tamper-proof adhesive that leaves a checkerboard pattern when label is removed
- Excellent smear/scratch resistance
- · Excellent durability and chemical resistance
- Retains void characteristic at temperatures up to 80° C
- Available in silver (05662RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	Silver gloss polyester	2.0 mil
Adhesive	Permanent, tamper- evident acrylic-based	0.8 mil
Liner	50 lb. semi-bleached, kraft stock	3.2 mil
	TOTAL ± 10%	7.0 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
50° F (10° C)	-40° F to 176° F (-40° C to 80° C)	72° F (22° C) at 50% RH

Expected Exterior Life

Not recommended for outdoor use

CHEMICAL RESISTANCE

Sugge		Suggest	ted Ribbon
	Chemical	5095	5100
Weak	Blood	•	•
	Body Fluid	•	•
	Salt Water	•	•
	Water	•	•
	Window Cleaner	•	•
Moderate	Alcohol	•	•
	Ammonia	•	•
	Bleach	•	•
	IPA	•	•
Harsh	Gasoline		
	Grease		
	Oil		
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

Recommended ○ Test in Your Application NR Not Recommended

80°C Void Performance on Stainless Steel

Dwell Time	% Voiding	% Adhesive Transfer
24 hours at RT	100%	95%

SUGGESTED APPLICATIONS

Product Identification



 Tamper evident security labels



Capital asset labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com