# ZEBRA CAPTURE YOUR EDGE

# **8000T-E Semi-Gloss Removable**

# Semi-gloss paper label with 30% recycled content

For environmentally conscious business owners who need to find solutions that contribute to achieving sustainability targets, Zebra partners with major material suppliers to offer new products and solutions as they come to market. 8000T-E Semi-Gloss Removable paper labels have a machine coated, semi-gloss appearance and contain 30% recycled post-consumer waste providing a more sustainable solution without compromising on quality.



## Print Confident. Print Quality. Print Zebra.

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pre-test our own line of thermal printing supplies to ensure consistent, optimized performance. We utilize an ISO 9001 certified, 23-point inspection process and consistent materials to ensure reliable performance from order-to-order. No matter when you order your labels, you can count on the same consistent performance.

## **Excellent Print Quality**

The removable adhesive features good adhesion and clean removability from many substrates including PET, PP, ABS, card and fibre board, aluminium, stainless steel or glass. Label application is possible at subzero temperatures it remains removable over a wide temperature range.

Minimum application temperature of -15°C and service temperature range from -30°C to 80°C.

## Sustainibility

Contribute to your sustainability goals without compromising on quality with 8000T-E Semi-Gloss Deep Removable.

# **Specifications**

RM Number	10026934RM
Facestock	Semi-gloss white paper with 30% recycled content 64 microns
Adhesive	Removable acrylic adhesive 12 microns
Liner	54gsm glassine liner 46 microns
Total Thickness (±10%)	122 microns
Environment	Indoor use; cold temperature compatible
Temperature Perfori	nance
Minimum Application Temperature <sup>1</sup>	-15° C
Service Temperature Range <sup>2</sup>	-30° C to 80° C
Recommended Print	ters and Ribbons
Printers	Mobile, desktop, mid-range and high performance thermal printers
Ribbons	2300 Wax 2100 High Performance Wax 3400 High Performance Wax Resin 3200 Premium Wax Resin
Adhesive Strength	
Corrugate	N/A
Steel	N/A
Polycarbonate	N/A
Polyethylene	N/A
Chemical Resistance	•
Weak Chemicals	N/A
Moderate Chemicals	N/A
Harsh Chemicals	N/A
Extreme Chemicals	N/A
UL/cUL Certified Ma	terials with this Ribbon
List materials with a common between them	N/A
Regulatory and Com	unliam an

Product Performance and Suitability	
Recommended storage conditions	I year duration when stored at 20° C to 25° C at 40 to 50% RH
Expected life span in application <sup>3</sup>	Indoor use, for 1 year+
Sample Part Number	SAMPLE26934

- 1. When the label is applied, the environment and surface should be above this temperature.
- 2. Following correct application and appropriate dwell time (usually 24 hrs) the media will withstand this temperature range.
- Following correct application and appropriate dwell time (usually 24 hrs) we expect, but do not warrant, a life span as indicated.
   Specifications are subject to change without notice.

## Markets and Applications

## Logistics

 Removable labeling for boxes, totes and bins

#### Warehousing

· Product Identification

#### Retail

 Removable Price, promotional or shelf edge labeling

## Manufacturing

 Removable WIP Labels



reduction factor of 2 or higher

Contains 30% post consumer waste recycled material

alternatively separated by a functional barrier Not recommended for window labeling

Adhesive complies with European food regulations and BfR Recommendation XIV for direct contact with dry, moist and fatty foodstuffs which have a

Adhesive complies with FDA 175.105 for direct contact with dry foodstuffs, or