

# 8000T GHS Vinyl

## **FEATURES**

- Thermal transfer white matte vinyl label with a permanent acrylic adhesive (10017748RM)
- · Excellent flexibility for curved surfaces
- Adhesive system designed to bond well to painted steel, fiber and plastic drums
- · Excellent durability and chemical resistance
- Meets BS 5609 Section 2 and Section 3 compliance when paired with Zebra's 5095 and Red Resin ribbons

### **MATERIAL CONSTRUCTION**

Component	Description	Caliper
Facestock	White matte vinyl	3.5 mil
Adhesive	Permanent, acrylic- based	1.0 mil
Liner	50 lb. semi-bleached, kraft stock	3.2 mil
	TOTAL ± 10%	7.7 mil

### **TEMPERATURE PERFORMANCE**

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
10° F (-12° C)	-40° F to 176° F (-40° C to 80° C)	72° F (22° C) at 50% RH

# **Expected Exterior Life** 2 years

### **CHEMICAL RESISTANCE**

	Suggested Ribbon		
	Chemical	5095	Red Resin
Weak	Blood	•	•
	Body Fluid	•	•
	Salt Water	•	•
	Water	•	•
	Window Cleaner	•	•
Moderate	Alcohol	•	•
	Ammonia	•	•
	Bleach	•	•
	IPA	•	•
Harsh	Gasoline		
	Grease		
	Oil		
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

Recommended
 Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

### For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.

### SUGGESTED APPLICATIONS

Chemical drum labeling

