
## PolyPro 3000T High-Tack

# ZEBRA


#### **FEATURES**

- Thermal transfer, matte polypropylene label with a high-tack permanent acrylic adhesive
- Good smear/scratch resistance
- · Excellent chemical resistance
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (65310RM)

#### MATERIAL CONSTRUCTION



#### ADHESIVE STRENGTH



#### **TEMPERATURE PERFORMANCE**

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
32°F	-75°F to 200°F	72° F (22° C)
(0°C)	(-59°C to 93°C)	at 50% RH

#### EXPECTED EXTERIOR LIFE

18 months

#### CHEMICAL RESISTANCE

Chemical		Suggested Ribbon		
		6100	3200	6200
Weak	Blood	•	•	•
	Body Fluid	•	•	•
	Salt Water	•	•	•
	Water	•	•	•
	Window Cleaner	•	•	•
Moderate	Alcohol	•	•	•
	Ammonia	•	•	•
	Bleach	•	•	•
	IPA	•	•	•
Harsh	Gasoline		•	•
	Grease		•	•
	Oil		•	•
Extreme	Acetone	•	•	•
	IR Reflow	•	•	•
	MEK	•		
	TCE	•	•	•
	Xylene	•	•	•

Recommended - Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.


#### For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.



### APPLICATIONS





Test tube labeling



