

PolyPro 4000D Label

Direct thermal matte polypropylene label with an all-temp acrylic adhesive

Optimal for applications where added durability over paper is needed due to moisture exposure or clean removability is required, Zebra's PolyPro 4000D label delivers. This direct thermal white polypropylene label is engineered to provide high print quality and durability at an economical price. Its all-temperature permanent acrylic adhesive can be applied to surfaces as cold as -40°F/-40° C and meets FDA 175.105 for indirect food contact requirements. It is suitable for fan-folding. And with Zebra's legacy of craftsmanship and durability, you can count on optimized performance – with each and every label. PolyPro 4000D labels are recommended for a wide variety of labeling applications, including cold storage, package labeling and indirect food labeling.



Print Confident. Print Quality. Print Zebra.

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pre-test our own line of thermal printing supplies to ensure consistent, optimized performance. We utilize an ISO 9001 certified, 23-point inspection process and consistent materials to ensure reliable performance from order-to-order. No matter when you order your labels, you can count on the same consistent performance.

Moisture and tear resistant

The polypropylene facesheet will not break down when subjected to moisture. In addition, the material is tear-resistant, which is beneficial for applications requiring the removal of the entire label for replacement with a new label, such as with reusable totes, crates, shelving and more.

Optimized for use with food products and in cold environments

With its all-temperature permanent acrylic adhesive, these labels can be securely applied in temperatures as low as -40°F/-40° C and will remain adhered in temperatures of -65°F to 131°F/-54°C to 55°C, making them perfect for use on assets in cold environments. The adhesive meets FDA 175.105 for indirect food contact and can be applied to shrink wrap and other food packaging.

Customized for your application

Zebra can deliver PolyPro 4000D labels in just about any size, shape or label set configuration to meet the requirements of your application and process. In addition, our flexographic print presses can add pre-printed text, graphics and color.

PolyPro 4000D Label – economical moisture resistant polypropylene label delivering high-quality print, with an all-temp permanent adhesive to meet labeling in cold environments.
For more information, please visit www.zebra.com/barcodesupplies

Specifications

Material Construction	
Raw Material Number	65843RM
Facestock	Direct thermal matte white polypropylene 2.8 mil/71.1 microns
Adhesive	All-temp permanent acrylic adhesive 0.8 mil/20.32 microns
Liner	40 lb/50 gsm semi-bleached kraft liner 2.5 mil/63.5 microns
Total Thickness (+/-10%)	6.1 mil/154.9 microns
Environment	Indoor use
Temperature Performance	
Minimum Application Temperature ¹	-40° F/-40° C
Service Temperature Range ²	-65° F to 131° F/-54° C to 55° C
Recommended Printers and Ribbons	
Printers	Direct thermal printer; use Zebra desktop, industrial and mobile thermal printers for optimal performance
Ribbons	N/A
Adhesive Strength	
Corrugate	5 minute dwell time: 17 oz/in.
	24 hour dwell time: 18 oz/in.
Steel	5 minute dwell time: 49 oz/in.
	24 hour dwell time ³
Polycarbonate	5 minute dwell time: 57 oz/in.
	24 hour dwell time ³
Polyethylene	5 minute dwell time: 26 oz/in.
	24 hour dwell time: 46 oz/in.
Chemical Resistance	
Weak Chemicals	
Blood	Test in your application
Body Fluid	Test in your application
Salt Water	Test in your application
Water	Test in your application
Window Cleaner	Test in your application
Moderate Chemicals	
Alcohol	Not recommended
Ammonia	Not recommended
Bleach	Not recommended
IPA	Not recommended
Harsh Chemicals	
Gasoline	Not recommended
Grease	Not recommended
Oil	Not recommended

Extreme Chemicals	
Acetone	Not recommended
IR Reflow	Not recommended
MEK	Not recommended
TCE	Not recommended
Xylene	Not recommended

Regulatory and Compliance	
FDA 175.105 for direct contact with dry foodstuffs, or alternatively separated by a functional barrier	

Product Performance and Suitability	
Recommended storage conditions	6 months duration when stored at 72° F/22° C at 50% RH
Expected life span in application ⁴	Indoor up to 1 year

Material Testing in End Application	
The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.	

Warranty	
Supplies are warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For the complete warranty statement, please visit www.zebra.com/warranty .	

Footnotes	
1.	When the label is applied, the environment and surface should be above this temperature.
2.	Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range.
3.	Attraction between adhesive and surface is so great that the facestock rips.
4.	Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated.

Markets and Applications

- Warehousing**
- Cold-storage labeling
 - Package labeling
- Other**
- Indirect food labeling



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
zebra.com/locations
la.contactme@zebra.com