

ZEBRA

PolyPro 4000T 7.0 mil Tag

FEATURES

- · Thermal transfer, matte polypropylene 7.0 mil tag
- · Good smear/scratch resistance
- · Some chemical resistance
- Available in white (65533RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White matte topcoated polypropylene	7.0 mil
	TOTAL ± 10%	7.0 mil

FACESTOCK TENSILE STRENGTH

Machine direction: 6700 psiTransverse direction: 5700 psi

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions	
NA	-40° F to 200° F (-40° C to 93° C)	72° F (22° C) at 50% RH	

EXPECTED EXTERIOR LIFE

l vear

CHEMICAL RESISTANCE

Blood Body Fluid Salt Water Window Cleaner Alcohol Ammonia Bleach IPA Gasoline 6100 3200 6200 6200			Suggested Ribbon		
Body Fluid Salt Water Water Window Cleaner Alcohol Ammonia Bleach IPA Gasoline		Chemical	6100	3200	6200
Salt Water Water Window Cleaner Alcohol Ammonia Bleach IPA Gasoline	Weak	Blood	•	•	•
Water Window Cleaner Alcohol Ammonia Bleach IPA Gasoline		Body Fluid	•	•	•
Water Window Cleaner Alcohol Ammonia Bleach IPA Gasoline		Salt Water	•	•	•
Alcohol Ammonia Bleach IPA Gasoline		Water	•	•	•
Ammonia Bleach IPA Gasoline		Window Cleaner	•	•	•
IPA • • • • • • • • • • • • • • • • • • •	a)	Alcohol	•	•	•
IPA • • • • • • • • • • • • • • • • • • •	erate	Ammonia	•	•	•
IPA • • • • • • • • • • • • • • • • • • •	Mode	Bleach	•	•	•
Gasoline		IPA	•	•	•
<u>w</u>	Harsh	Gasoline			
Grease Grease		Grease			
Oil		Oil			
Acetone	Extreme	Acetone	•	•	•
و IR Reflow •		IR Reflow			
MEK • •		MEK	•	•	•
TCE •		TCE	•	•	•
Xylene		Xylene	•	•	•

Recommended
 Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

 Self-locking tags for greenhouse and nursery use



Outdoor storage tags for wire, cable and fabricated parts



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com