

### **ZEBRA**

# PolyPro 4000T 8.5mil Tag

#### **FEATURES**

- Thermal transfer, smudgeproof Kimdura® topcoated 8.5 mil polypropylene tag
- Good smear/scratch resistance
- Excellent chemical resistance
- · Available in white (05127RM)

#### **MATERIAL CONSTRUCTION**

Component	Description	Caliper
Facestock	White matte topcoated polypropylene	8.5 mil
	TOTAL ± 10%	8.5 mil

#### **FACESTOCK TENSILE STRENGTH**

Machine direction: 54 psiTransverse direction: 160 psi

#### **TEMPERATURE PERFORMANCE**

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions	
NA	-40° F to 200° F (-40° C to 93° C)	72° F (22° C) at 50% RH	

## **EXPECTED EXTERIOR LIFE** 2 year

#### **CHEMICAL RESISTANCE**

		Suggested Ribbon		
	Chemical	6100	3200	6200
Weak	Blood	•	•	•
	Body Fluid	•	•	•
	Salt Water	•	•	•
	Water	•	•	•
	Window Cleaner	•	•	•
4	Alcohol	•	•	•
Moderate	Ammonia	•	•	•
	Bleach	•	•	•
	IPA	•	•	•
Harsh	Gasoline			
	Grease			
	Oil			
Extreme	Acetone	•	•	•
	IR Reflow			
	MEK	•	•	
	TCE	•	•	
	Xylene	•	•	•

■ Recommended ■ Test in Your Application NR Not Recommended

### SUGGESTED APPLICATIONS

 Self-locking tags for greenhouse and nursery use



Outdoor storage tags for wire, cable and fabricated parts



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

#### For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com