

### **ZEBRA**

# PolyPro 4000T High-Tack


#### **FEATURES**

- Thermal transfer, matte Kimdura polypropylene label with a permanent acrylic adhesive
- · Good smear/scratch resistance
- Excellent chemical resistance
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (05440RM)

#### **MATERIAL CONSTRUCTION**

Component	Description	Caliper	
Facestock	White matte topcoated polypropylene	3.8 mil	
Adhesive	High-tack, acrylic-based	1.0 mil	
Liner	50 lb. semi-bleached, kraft stock	3.2 mil	
	TOTAL ± 10%	8.0 mil	

#### **ADHESIVE STRENGTH**



#### **TEMPERATURE PERFORMANCE**

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions	
35°F	-65°F to 200°F	72° F (22° C)	
(2°C)	(-54°C to 121°C)	at 50% RH	

#### **Expected Exterior Life**

2 years

#### **CHEMICAL RESISTANCE**

		Suggested Ribbon		
Chemical		5555	6100	5586
Weak	Blood	•	•	•
	Body Fluid	•	•	•
	Salt Water	•	•	•
	Water	•	•	•
	Window Cleaner	•	•	•
Moderate	Alcohol	•	•	•
	Ammonia	•	•	•
	Bleach	•	•	•
	IPA	•	•	•
Harsh	Gasoline			
	Grease			
	Oil			
Extreme	Acetone	•	•	•
	IR Reflow			
	MEK	•		
	TCE	•	•	•
	Xylene	•	•	•

## SUGGESTED APPLICATIONS

Automotive labeling



Medical Device labeling



· Product identification



Recommended
 Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

#### For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com