

Z-Endure™ 3000T

FEATURES

- Thermal transfer, acrylic label with a reflective glass bead coating and a high-performance permanent acrylic adhesive
- Excellent smear/scratch resistance
- · Excellent durability and chemical resistance
- Special acrylic film offers 7 year outdoor durability
- Available in white (05197RM), orange (05226RM), red (05228RM) and yellow (05229RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	Acrylic film with reflective glass bead coating	4.0 mil
Adhesive	High-performance permanent acrylic based	0.9 mil
Liner	50 lb. bleached, kraft	3.1 mil
	TOTAL ± 10%	8.0 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
50° F (10° C)	-40° F to 176° F (-40° C to 80° C)	72° F (22° C) at 50% RH

Expected Exterior Life 7 years

CHEMICAL RESISTANCE

Chemical		Suggested Ribbon	
		6200	5100
Weak	Blood	•	•
	Body Fluid	•	•
	Salt Water	•	•
	Water	•	•
	Window Cleaner	•	•
Moderate	Alcohol	•	•
	Ammonia	•	•
	Bleach	•	•
	IPA	•	•
Harsh	Gasoline		
	Grease		
	Oil		
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

[•] Recommended • Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

 Long-term outdoor safety warning labels/signs



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies