SUGGESTED APPLICATIONS

Product identification



Compliance labeling



Work-in-process

Food labeling

ZEBRA

FEATURES

· Direct thermal, smooth, paper label with a permanent acrylic adhesive


Z-Select 4000D

- Good print quality up to 10 in/sec
- Meets FDA 175.105 for indirect food contact requirements
- Limited resistance to moisture or abrasion
- Available in white (05176RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth coated direct thermal paper	3.2 mil
Adhesive	All-temp, acrylic-based	0.8 mil
Liner	40 lb. semi-bleached, kraft stock	2.3 mil
	TOTAL ± 10%	6.3 mil

ADHESIVE STRENGTH



^{*}Attraction between adhesive and surface is so great that the facestock rips.

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
-20° F	-65° F to 140° F	72° F (22° C)
(-29° C)	(-54° C to 60° C)	at 50% RH

Expected Exterior Life

Not recommended for outdoor use

CHEMICAL RESISTANCE

	Chemical	Direct Thermal
	Blood	NR
×	Body Fluid	NR
Weak	Salt Water	
_	Water	
	Window Cleaner	NR
(I)	Alcohol	NR
Moderate	Ammonia	NR
Nod	Bleach	NR
	IPA	NR
_	Gasoline	NR
Harsh	Grease	NR
_	Oil	NR
	Acetone	NR
ne	IR Reflow	NR
Extreme	MEK	NR
û	TCE	NR
	Xylene	NR

Recommended
Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies