

### **ZEBRA**

# **Z-Select 4000T Removable**


#### **FEATURES**

- Thermal transfer, premium, ultra smooth, paper label with a removable acrylic adhesive
- Excellent high speed print quality
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (05233RM)

#### **MATERIAL CONSTRUCTION**

Component	Description	Caliper
Facestock	White smooth topcoated paper	3.2 mil
Adhesive	Removable, acrylic- based	0.8 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
	TOTAL ± 10%	6.5 mil

#### **ADHESIVE STRENGTH**



#### **TEMPERATURE PERFORMANCE**

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
40° F (4° C)	-65° F to 180° F (-54° C to 82° C)	72° F (22° C) at 50% RH

#### **Expected Exterior Life**

Not recommended for outdoor use

#### **CHEMICAL RESISTANCE**

		Suggested Ribbon		
	Chemical	6000	2000	6100
Weak	Blood			
	Body Fluid			
	Salt Water			
	Water			
	Window Cleaner			
Moderate	Alcohol	NR	NR	NR
	Ammonia	NR	NR	NR
	Bleach	NR	NR	NR
	IPA	NR	NR	NR
Harsh	Gasoline	NR	NR	NR
	Grease	NR	NR	NR
	Oil	NR	NR	NR
Extreme	Acetone	NR	NR	NR
	IR Reflow	NR	NR	NR
	MEK	NR	NR	NR
	TCE	NR	NR	NR
	Xylene	NR	NR	NR

Recommended ○ Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

Labeling of packaging materials



Work in process



Food labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

#### For more information, visit www.zebra.com/supplies