Z-Supreme 2000T

FEATURES

- Thermal transfer, gloss white polyimide label with a high-temp permanent acrylic adhesive
- Excellent smear/scratch resistance
- Excellent durability and chemical resistance
- Z-Supreme 2000T is UL approved when used
- with 5095 or 5100 ribbon
 May be used in RoHS compliant (lead-free) wave solder processes for printed circuit boards
- Available in 2 mil white with a paper liner (68165RM), 2 mil white with poly liner (68077RM), 1 mil white with a paper liner (68080RM) or 1 mil white with poly liner (68079RM)

MATERIAL CONSTRUCTION (68165RM)

Component	Description	Caliper
Facestock	White coated polyimide	2.8 mil
Adhesive	High-temperature, acrylic-based	1.5 mil
Liner	50 lb. white glassine	2.7 mil
	TOTAL ± 10%	7.0 mil

Time/Temperature Performance:

Temperature	Time
1000 F (538 C)	5 seconds
662 F (350 C)	2 minutes
626 F (330 C)	5 minutes
500 F (260 C)	2 hours

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
50° F (10° C)	-40° F to 500° F (-40° C to 260° C)	72° F (22° C) at 50% RH

Expected Exterior Life

2 years

CHEMICAL RESISTANCE

	Chemical	Suggested Ribbon 5100
Weak	Blood	•
	Body Fluid	•
	Salt Water	•
	Water	•
	Window Cleaner	•
Moderate	Alcohol	•
	Ammonia	•
	Bleach	•
	IPA	•
Harsh	Gasoline	
	Grease	
	Oil	
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

Recommended - Test in Your Application NR Not Recommended



For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.



SUGGESTED APPLICATIONS

Bottom-side lead-free
 PCB labeling



Product identification



· Automotive labeling



Extreme high temperature applications up to 1000°F (see time/temperature chart)

