Afti.

ZEBRA

Z-Supreme 3000T

FEATURES

- Thermal transfer, white, matte polyimide label with a high-temp permanent acrylic adhesive
- · Excellent smear/scratch resistance
- Unparalleled durability and chemical resistance
- May be used in wave solder processes for printed circuit boards
- Available in white (65080RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White, matte coated polyimide	2.2 mil
Adhesive	High-temperature, acrylic-based	1.2 mil
Liner	50 lb. semi-bleached, kraft stock	3.0 mil
	TOTAL ± 10%	6.4 mil

Time/Temperature Performance

Temperature	Time	
1000 F (583 C)	5 seconds	
662 F (350 C)	2 minutes	
626 F (330 C)	5 minutes	
500 F (260 C)	2 hours	

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
50° F (10° C)	-40° F to 482° F (-40° C to 250° C)	72° F (22° C) at 50% RH

Expected Exterior Life

2 years

CHEMICAL RESISTANCE

	Chemical	Suggested Ribbon 5100
	Blood	•
J	Body Fluid	•
Weak	Salt Water	•
	Water	•
	Window Cleaner	•
	Alcohol	•
Moderate	Ammonia	•
Mod	Bleach	•
	IPA	•
	Gasoline	
Harsh	Grease	
	Oil	
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

■ Recommended ■ Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

Bottom-side lead-free
PCB labeling



· Product identification



Automotive labeling



 Extreme high temperature applications up to 482°F



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies