

Z-Xtreme 2000T Removable Label

Thermal transfer, matte polyester label with a removable acrylic adhesive

Optimal for the labeling of assets in more challenging environments, including those that require mild chemical processing, Zebra's Xtreme 2000T Removable label delivers. This thermal transfer, white, matte polyester label is engineered to provide reliable print quality and durability. When paired with Zebra's 6200 wax/resin or 6100, 5095 and 3200 resin ribbons, you get smear and scratch resistant print and durability against weak chemicals, such as blood, body fluids, salt water, water and window cleaner. It is suitable for fan-folding. And with Zebra's legacy of craftsmanship and durability, you can count on optimized performance – with each and every label. Z-Xtreme 2000T Removable labels are recommended for a wide variety of labeling applications, including shelf labeling and work in progress.



Print Confident. Print Quality. Print Zebra

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pre-test our own line of thermal printing supplies to ensure consistent, optimized performance. We utilize an ISO 9001 certified, 23-point inspection process and consistent materials to ensure reliable performance from order-to-order. No matter when you order your labels, you can count on the same consistent performance.

Some smear and scratch and good durability and chemical resistance

Z-Xtreme 2000T Removable labels, when paired with Zebra's 6200, 6100, 5095 or 3200 ribbons, offer good adhesive quality and print durability to smearing and scratching, ensuring your assets remain identifiable throughout their useful life. The label will remain readable and intact when subjected to weak chemicals, such as blood, body fluid, salt water, water and window cleaner. Once applied, this label can withstand temperatures up to 302° F/150° C, making it a reliable choice to identify products which require high-heat processing during manufacturing and those that will be subjected to heat when in use, such as some food preparation equipment.

Customized for your application.

Zebra can deliver Z-Xtreme 2000T Removable labels in multiple sizes, shapes or label set configurations to meet the requirements of your application and process. In addition, our flexographic print presses can add pre-printed text, graphics and color.

Z-Xtreme 2000T Removable Label – High-heat, smear and scratch resistant labels with mild chemical resistance and high-performance acrylic adhesive for more challenging applications.
For more information, please visit www.zebra.com/supplies

Specifications

Material Construction	
Raw Material Number	66760RM White
Facestock	Thermal transfer, white, matte, polyester 2.3 mil/58.42 microns
Adhesive	Removable acrylic-based adhesive 1.0 mil/25.4 microns
Liner	50 lb semi-bleached, kraft stock 3.2 mil/81.28 microns
Total Thickness (+/-10%)	6.5 mil/165.1 microns
Environment	Indoor use; Outdoor use up to 3 years
Temperature Performance	
Minimum Application Temperature ¹	50° F/10° C
Service Temperature Range ²	-40° F to 302° F/-40° C to 150° C
Recommended Printers and Ribbons	
Printers	Thermal transfer printer (ribbon required); use Zebra desktop, mid-range and high-performance thermal printers for optimal performance
Ribbons	Compatible with Zebra 6200, 6100, 5095 and 3200 resin ribbons for optimal performance
Adhesive Strength	
Stainless Steel	5 minute dwell time: 15 oz/in.
	24 hour dwell time: 20 oz/in.
Polycarbonate	5 minute dwell time: 16 oz/in.
	24 hour dwell time: 23 oz/in.
Polyethylene	5 minute dwell time: 4 oz/in.
	24 hour dwell time: 8 oz/in.
Facestock Tensile Strength	
Machine Direction	18,000 psi
Transverse Direction	22,000 psi
Chemical Resistance	
Weak Chemicals	
Blood	6200, 6100, 5095 and 3200: Recommended
Body Fluid	6200, 6100, 5095 and 3200: Recommended
Salt Water	6200, 6100, 5095 and 3200: Recommended
Water	6200, 6100, 5095 and 3200: Recommended
Window Cleaner	6200, 6100, 5095 and 3200: Recommended

Moderate Chemicals	
Alcohol	6200, 6100, 5095 and 3200: Test in your Application
Ammonia	6200, 6100, 5095 and 3200: Test in your Application
Bleach	6200, 6100, 5095 and 3200: Test in your Application
IPA	6200, 6100, 5095 and 3200: Test in your Application
Harsh Chemicals	
Gasoline	Not recommended
Grease	Not recommended
Oil	Not recommended
Extreme Chemicals	
Acetone	Not recommended
IR Reflow	Not recommended
MEK	Not recommended
TCE	Not recommended
Xylene	Not recommended
Regulatory Compliance	
UL with 6200, 6100, 5095 and 3200 ribbons; UL-recognized for indoor use	
Product Performance and Suitability	
Recommended storage conditions	72° F/22° C at 50% RH
Expected life span in application ³	Indoor and outdoor up to 3 years
Material Testing in End Application	
The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.	
Warranty	
Supplies are warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For the complete warranty statement, please visit www.zebra.com/warranty .	
Footnotes	
1.	When the label is applied, the environment and surface should be above this temperature.
2.	Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range.
3.	Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated.

Markets and Applications

- Manufacturing**
- Shelf labeling
 - Work in progress



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
zebra.com/locations
la.contactme@zebra.com