

ZDesigner Windows Printer Driver Release Notes

Version 5.1.17.7412

Table of Contents

[Welcome](#)
[Supported Operating Systems](#)
[Installation](#)
[Supported Printers](#)
[Tips & Advice](#)
[Known Issues](#)
[Change Log](#)
[Technical Support](#)
[Software Updates](#)

Welcome

This version of the ZDesigner Windows Printer driver offers many features and user conveniences. Currently shipping Zebra printers using CPCL, EPL2 or ZPL II can now be driven using one set of driver files. A common user interface for all of the printer languages makes it easy to work with any of the supported printers listed below. Utilities, such as a Font and Graphic Downloader and a Status Monitor are included.

[Back to top](#)

Supported Operating Systems

This driver is supported on the following Microsoft 32-bit and 64-bit operating systems:

- Windows 10 desktop editions
- Windows 11 desktop editions
- Windows Server 2016
- Windows Server 2019
- Windows Server 2022

Windows is a registered trademark of Microsoft Corporation.

[Back to top](#)

Installation

How to Install Zebra Printer Drivers.

Drivers can be installed from the Windows "Add Printer Wizard" or using the Installation Utility that came with the driver. NOTE: your user account must have the

necessary rights to install a driver otherwise contact your system administrator for further assistance.

To install using the Installation Utility:

1. Uncompress the driver files. Be sure to note the location that the files are placed into.
2. Run the PrnInst.exe utility.
3. Follow the prompts to select the printer model and port that you will be using.
4. The Utility will ask if you want to install the Font and Graphic Downloader and Status Monitor - select these items if they are needed in your application.
5. The Utility will install the appropriate files.

To install the driver using the Windows "Add Printer Wizard".

1. Uncompress the driver files. Be sure to note the location that the files are placed into.
2. Using the START menu select "Settings" and then "Printers". The Printers folder will open up.
3. Double click on "Add Printer" and follow the prompts to begin the installation process.
4. When you come to the dialog screen that lists Manufacturers and Printers, select "Have disk".
5. Browse to the location that contains the uncompressed driver files.
6. Select the ZBRN.inf file in the ZBRN folder and click "OK" to continue.
7. Select your printer model from the list of supported printers and click the Next button to continue.
8. If your printer is connected via a RS-232 serial connection, select "No" to the question "Would you like to print a test page?". This is suggested to avoid an error message in case you have not configured the port on the computer to match the serial settings on the printer. If your printer is connected via a parallel port and is ready to print, select "Yes" to print the test page.
9. Follow the remaining prompts to complete the Wizard. Once the install is done your printer driver is now installed and ready for use.

[Back to top](#)

Supported Printers

The following Zebra printers are supported in this version:

105SL 203DPI
105SL 300DPI
105SLPlus-203dpi ZPL
105SLPlus-300dpi ZPL
110PAX4 203DPI
110PAX4 300DPI
110Xi4 203 dpi
110Xi4 300 dpi
110Xi4 600 dpi

110XiIII Plus 200DPI
110XiIII Plus 300DPI
110XiIII Plus 600DPI
140Xi4 203 dpi
140XiIII Plus
170PAX4 203DPI
170PAX4 300DPI
170Xi4 203 dpi
170Xi4 300 dpi
170XiIII Plus
170XiIII Plus 200DPI
220Xi4 203 dpi
220Xi4 300 dpi
220XiIII Plus
220XiIII Plus 300DPI
888-DT
888-TT
EZ 320
GC420d
GC420d (EPL)
GC420t
GC420t (EPL)
GK420d
GK420d (EPL)
GK420E (EPL)
GK420E (ZPL)
GK420t
GK420t (EPL)
GK420t Plus (EPL)
GK420t Plus (ZPL)
GK888d
GK888d (EPL)
GK888E (EPL)
GK888E (ZPL)
GK888t
GK888t (EPL)
GT800 (EPL)
GT800 (ZPL)
GT800 Plus (EPL)
GT800 Plus (ZPL)
GT800-300dpi EPL
GT800-300dpi ZPL
GX420d
GX420d (EPL)
GX420s
GX420s (EPL)
GX420t
GX420t (EPL)
GX430t
GX430t (EPL)
HC100 300 dpi
iMZ220
iMZ220 (ZPL)
iMZ320

iMZ320 (ZPL)
KR403
LP 2824
LP 2824 Plus (EPL)
LP 2824 Plus (ZPL)
LP 2844
LP 2844-Z
Mobile Printer
MZ 220
MZ 320
P4T (CPCL)
P4T (ZPL)
QL 220/QL 220 Plus
QL 320/QL 320 Plus
QL 420/QL 420 Plus
QLn220
QLn220 (ZPL)
QLn320
QLn320 (ZPL)
QLn420 (CPCL)
QLn420 (ZPL)
R110PAX4 LH-203DPI
R110PAX4 LH-300DPI
R110PAX4 RH-203DPI
R110PAX4 RH-300DPI
R110Xi 200DPI
R110Xi 300DPI
R110Xi HF 200DPI
R110Xi HF 300DPI
R110Xi4 203 dpi
R110Xi4 300 dpi
R110Xi4 600 dpi
R170Xi 200DPI
R170Xi 300DPI
R2844-Z
RP4T (ZPL)
RW 220
RW 420
RW4-PS
RZ400 200 dpi
RZ400 300 dpi
RZ600 200 dpi
RZ600 300 dpi
S4M-203dpi EPL
S4M-203dpi ZPL
S4M-300dpi ZPL
TLP 2824
TLP 2824 Plus (EPL)
TLP 2824 Plus (ZPL)
TLP 2844
TLP 2844-Z
TLP 3842
TLP 3844-Z
ZD220-203dpi EPL

ZD220-203dpi ZPL
ZD230-203dpi EPL
ZD230-203dpi ZPL
ZD410-203dpi EPL
ZD410-203dpi ZPL
ZD410-300dpi EPL
ZD410-300dpi ZPL
ZD411-203dpi EPL
ZD411-203dpi ZPL
ZD411-300dpi EPL
ZD411-300dpi ZPL
ZD420-203dpi EPL
ZD420-203dpi ZPL
ZD420-300dpi EPL
ZD420-300dpi ZPL
ZD421-203dpi EPL
ZD421-203dpi ZPL
ZD421-300dpi EPL
ZD421-300dpi ZPL
ZD421CN-300dpi EPL
ZD421CN-300dpi ZPL
ZD500-203dpi EPL
ZD500-203dpi ZPL
ZD500-300dpi EPL
ZD500-300dpi ZPL
ZD500R-203dpi ZPL
ZD500R-300dpi ZPL
ZD510-300dpi ZPL
ZD511-300dpi ZPL
ZD611-203dpi EPL
ZD611-203dpi ZPL
ZD611-300dpi EPL
ZD611-300dpi ZPL
ZD611R-203dpi ZPL
ZD611R-300dpi ZPL
ZD620-203dpi EPL
ZD620-203dpi ZPL
ZD620-300dpi EPL
ZD620-300dpi ZPL
ZD621-203dpi EPL
ZD621-203dpi ZPL
ZD621-300dpi EPL
ZD621-300dpi ZPL
ZD621R-203dpi ZPL
ZD621R-300dpi ZPL
ZD888-203dpi EPL
ZD888-203dpi ZPL
ZE500-4 LH-203dpi ZPL
ZE500-4 LH-300dpi ZPL
ZE500-4 RH-203dpi ZPL
ZE500-4 RH-300dpi ZPL
ZE500-6 LH-203dpi ZPL
ZE500-6 LH-300dpi ZPL
ZE500-6 RH-203dpi ZPL

ZE500-6 RH-300dpi ZPL
ZE500R-4 LH-203dpi ZPL
ZE500R-4 LH-300dpi ZPL
ZE500R-4 RH-203dpi ZPL
ZE500R-4 RH-300dpi ZPL
ZE511 LH-203dpi ZPL
ZE511 LH-300dpi ZPL
ZE511 LH-600dpi ZPL
ZE511 RH-203dpi ZPL
ZE511 RH-300dpi ZPL
ZE511 RH-600dpi ZPL
ZE511R LH-203dpi ZPL
ZE511R LH-300dpi ZPL
ZE511R LH-600dpi ZPL
ZE511R RH-203dpi ZPL
ZE511R RH-300dpi ZPL
ZE511R RH-600dpi ZPL
ZE521 LH-203dpi ZPL
ZE521 LH-300dpi ZPL
ZE521 RH-203dpi ZPL
ZE521 RH-300dpi ZPL
ZE521R LH-203dpi ZPL
ZE521R LH-300dpi ZPL
ZE521R RH-203dpi ZPL
ZE521R RH-300dpi ZPL
ZM400 200 dpi (EPL)
ZM400 200 dpi (ZPL)
ZM400 300 dpi (ZPL)
ZM400 600 dpi (ZPL)
ZM600 200 dpi (EPL)
ZM600 200 dpi (ZPL)
ZM600 300 dpi (ZPL)
ZQ112 (CPCL)
ZQ120 (CPCL)
ZQ120 Plus (CPCL)
ZQ210 (CPCL)
ZQ220 (CPCL)
ZQ220 Plus (CPCL)
ZQ310 (CPCL)
ZQ310 (ZPL)
ZQ310 Plus (CPCL)
ZQ310 Plus (ZPL)
ZQ320 (CPCL)
ZQ320 (ZPL)
ZQ320 Plus (CPCL)
ZQ320 Plus (ZPL)
ZQ510 (CPCL)
ZQ510 (ZPL)
ZQ511 (CPCL)
ZQ511 (ZPL)
ZQ511R (ZPL)
ZQ520 (CPCL)
ZQ520 (ZPL)
ZQ521 (CPCL)

ZQ521 (ZPL)
ZQ521R (ZPL)
ZQ610 (CPCL)
ZQ610 (ZPL)
ZQ610 Plus (CPCL)
ZQ610 Plus (ZPL)
ZQ620 (CPCL)
ZQ620 (ZPL)
ZQ620 Plus (CPCL)
ZQ620 Plus (ZPL)
ZQ630 (CPCL)
ZQ630 (ZPL)
ZQ630 Plus (CPCL)
ZQ630 Plus (ZPL)
ZQ630R (ZPL)
ZQ630R Plus (ZPL)
ZR118 (CPCL)
ZR138 (CPCL)
ZR318 (CPCL)
ZR318 (ZPL)
ZR328 (CPCL)
ZR328 (ZPL)
ZR328 Plus (CPCL)
ZR328 Plus (ZPL)
ZR338 (CPCL)
ZR338 (ZPL)
ZR628 (CPCL)
ZR628 (ZPL)
ZR638 (CPCL)
ZR638 (ZPL)
ZR658 (CPCL)
ZR658 (ZPL)
ZR668 (CPCL)
ZR668 (ZPL)
ZR668 Plus (CPCL)
ZR668 Plus (ZPL)
ZT111-203dpi EPL
ZT111-203dpi ZPL
ZT111-300dpi ZPL
ZT210-200dpi EPL
ZT210-200dpi ZPL
ZT210-300dpi ZPL
ZT211-203dpi EPL
ZT211-203dpi ZPL
ZT211-300dpi ZPL
ZT220-200dpi EPL
ZT220-200dpi ZPL
ZT220-300dpi ZPL
ZT230-200dpi EPL
ZT230-200dpi ZPL
ZT230-300dpi ZPL
ZT231-203dpi EPL
ZT231-203dpi ZPL
ZT231-300dpi ZPL

ZT231R-203dpi ZPL
ZT231R-300dpi ZPL
ZT410-203dpi EPL
ZT410-203dpi ZPL
ZT410-300dpi ZPL
ZT410-600dpi ZPL
ZT410R-203dpi ZPL
ZT410R-300dpi ZPL
ZT410R-600dpi ZPL
ZT411-203dpi EPL
ZT411-203dpi ZPL
ZT411-300dpi ZPL
ZT411-600dpi ZPL
ZT411R-203dpi ZPL
ZT411R-300dpi ZPL
ZT411R-600dpi ZPL
ZT420-203dpi ZPL
ZT420-300dpi ZPL
ZT420R-203dpi ZPL
ZT420R-300dpi ZPL
ZT421-203dpi ZPL
ZT421-300dpi ZPL
ZT421R-203dpi ZPL
ZT421R-300dpi ZPL
ZT510-203dpi ZPL
ZT510-300dpi ZPL
ZT610-203dpi ZPL
ZT610-300dpi ZPL
ZT610-600dpi ZPL
ZT610R-203dpi ZPL
ZT610R-300dpi ZPL
ZT610R-600dpi ZPL
ZT620-203dpi ZPL
ZT620-300dpi ZPL
ZT620R-203dpi ZPL
ZT620R-300dpi ZPL

[Back to top](#)

Tips & Advice

1. Use the Use Printer Settings option on the Advanced Tab to stop the driver from sending the printer configuration and save configuration commands. This has the effect of improving throughput in some applications.
2. For ZPL printers, use the use ZIP compression option on the Other Settings dialog to cause the driver to create compressed graphics. This has the effect of improving throughput in some applications.
3. It is recommended that an Administrator account be used when installing the driver.
4. Microsoft Word splits strings into single characters. To avoid this select "Merge characters" option on driver's "Printer settings" tab.

5. The Status Monitor regularly checks the printer for current status information. When the driver is being used over a network connection, this can have the effect of consuming connection ports that would otherwise be used for accepting print jobs at the printer. If the Status Monitor is in use and you are experiencing a delay in printing, try right clicking over the Status Monitor in the system tray (by the clock) and closing the Status Monitor.

[Back to top](#)

Known Issues

1. The drivers will not print more than 32767 copies of a document. This is a Windows limitation.
2. Graphics print best when a monochrome image is used. Because Zebra printers are monochrome printers, color and grayscale images will be printed using the dithering method you select on the Options tab. There are four available dithering methods, each offering some control over the final printed image. However, monochrome images will print in a more predictable fashion.
3. When using Word, the application forces the driver to insert spaces into any edited line of text using the ZPL Font 0 (ZB:Zebra CG Triumvirate). If you save the document after editing the text, but before printing it, the spaces will not be inserted on the printed label.
4. Not all Applications will read internal font information from drivers. Some applications will not present the list of native fonts and bar codes even if the operating system is restarted after installing and the driver is set as the default driver. This is a limitation of some applications.
5. The Command Font Prefix and Suffix value are inserted before and after each character of text in Command Font when an EPL or CPCL printer driver is used. Microsoft Word splits strings into single characters. To avoid this, select "Merge characters" option on driver's "Printer settings" tab.
6. In Windows 7 and Windows 2008 R2, some applications do not allow the fonts that are native on the printer to be displayed as selectable when the user accesses the Properties of a field. In most applications they are displayed and selectable from the Fonts drop-down menu.
7. If Permissions on the computer do not allow the driver to write in the Registry, then the Command Fonts and/or Stocks Tabs in the driver dialogs will have buttons disabled. To change Command Fonts and Stocks, open the Printers folder the in Control Panel, select the printer and then open its "Printing Preferences". Then the user will be able to modify Command Fonts and Stocks. These properties are set per device and not per document.
8. When the passthrough start/end character combination includes the {} characters, data may not be passed through when using newer web browser versions including, but not limited to Internet Explorer®, Google Chrome™ and Firefox®. Use a start/end character combination that does not include {}.
9. The P4T and RP4T printers contain firmware supporting a subset of ZPL commands. As a result, when using the P4T or RP4T ZPL driver, some functionality in the tools section is not supported by the printer. The "Feed one label" option may not work and can be substituted by sending: **! U1 do "test.feed" "now"**.

10. When using ZebraDesigner Pro v2.5.0.x, the RFID Read and Print functionality is supported for Text and 1D barcode fields only. 2D barcode types are not supported.
11. Printers typically have different minimum label lengths for the different operation modes, e.g. tear-off, peel-off, cutter etc. The minimum label length/height that can be set in the driver applies to the operation mode having the shortest minimum label length. Refer to the technical specification of your printer model for the minimum label length of each operation mode.

[Back to top](#)

Change Log

Release Date	Version	Changes
08 Jan 2010	2.0	<p>Initial release of new platform. New features include:</p> <ul style="list-style-type: none">• Status Monitor<ul style="list-style-type: none">◦ For use with EPL and ZPL printers◦ Optionally installable when using the PrnInst.exe utility◦ Regularly checks printer status and displays an error message when an error occurs• Advanced TCP Port<ul style="list-style-type: none">◦ Provides a defined TCP port type• Tools tab:<ul style="list-style-type: none">◦ Simple method to send common printer commands.◦ Send File and Send Command options.◦ Supports all communication ports.• Use Printer Settings" option on Advanced Setup tab:<ul style="list-style-type: none">◦ Allows user to configure driver to not send printer settings• Inverse option on Advanced Setup tab:<ul style="list-style-type: none">◦ Allows user to cause the entire label to be printed in inverted format (white text on black background)• Passthrough feature on Other Settings dialog:<ul style="list-style-type: none">◦ Allows user to create blocks of commands to be sent to the printer unchanged by the driver.

		<ul style="list-style-type: none"> Control Character Substitution on the Other Settings dialog: <ul style="list-style-type: none"> Allows the ZPL driver to use the internal characters for the Format (^) and Control (~) characters On-screen barcode rendering, display only for design purposes
08 Jul 2011	2.6.63.02	<p>Update Release</p> <ul style="list-style-type: none"> Added support for the QLn Series and EZ 320 model. The Print Monitor will now be completed, even if the application is still running during the uninstall process. Memory Card options for G-Series printers have been expanded. Print positioning for EPL drivers in 180 degree rotated mode has been enhanced. Font and Graphic Downloader installation for R110Xi4 has been corrected. Set-Get-Do Commands formatting issues resolved. UI language translations for the Printer Install Wizard and Status Monitor have been updated. Spooler interactions for USB connected printers have been improved to handle situations where the printer has been disconnected.
15 Aug 2011	2.6.63.06	<p>Update Release</p> <ul style="list-style-type: none"> The "Send File" feature for Mobile printers has been corrected. The GX420s is now supported.
14 Sep 2011	2.6.63.12	<p>Update Release</p> <ul style="list-style-type: none"> The "Send and Store" feature for Mobile printers has been corrected.
03 Jan 2012	2.6.67.03	<p>Update Release</p> <ul style="list-style-type: none"> Corrected Russian translations.

		<ul style="list-style-type: none"> • Improved handling of file headers in the 'Send and Store File in Printer' function. • Added Stream option in advanced setup. • Added support for the following printer models: <ul style="list-style-type: none"> ◦ ZDesigner GC420d ◦ ZDesigner GC420d (EPL) ◦ ZDesigner GC420t ◦ ZDesigner GC420t (EPL) ◦ ZDesigner QLn220 (ZPL) ◦ ZDesigner QLn320 (ZPL) ◦ ZDesigner ZE500-4 LH-203dpi ZPL ◦ ZDesigner ZE500-4 LH-300dpi ZPL ◦ ZDesigner ZE500-4 RH-203dpi ZPL ◦ ZDesigner ZE500-4 RH-300dpi ZPL ◦ ZDesigner ZE500-6 LH-203dpi ZPL ◦ ZDesigner ZE500-6 LH-300dpi ZPL ◦ ZDesigner ZE500-6 RH-203dpi ZPL ◦ ZDesigner ZE500-6 RH-300dpi ZPL ◦ ZDesigner ZT210-200dpi ZPL ◦ ZDesigner ZT210-200dpi EPL ◦ ZDesigner ZT210-300dpi ZPL ◦ ZDesigner ZT220-200dpi ZPL ◦ ZDesigner ZT220-200dpi EPL ◦ ZDesigner ZT220-300dpi ZPL ◦ ZDesigner ZT230-200dpi ZPL ◦ ZDesigner ZT230-200dpi EPL ◦ ZDesigner ZT230-300dpi ZPL
02 Oct 2012	2.6.77.09	<p>Update Release</p> <ul style="list-style-type: none"> • Executable files are now signed with Zebra Technologies digital signature. • Corrected an issue where the GK888t EPL driver could not be set for direct thermal mode. • Corrected an issue where the GC420t EPL driver could not be set for thermal transfer mode. • Corrected an issue where print jobs were deleted from the Windows print queue when an out of media condition occurred and USB communication was used.

		<ul style="list-style-type: none"> Added the following printer models: <ul style="list-style-type: none"> 105SLPlus QLn420 iMZ220 iMZ320
25 Oct 2012	2.6.77.18	<p>Update Release</p> <ul style="list-style-type: none"> Updates to be Windows 8 compatible. Corrected iMZ320 model name. The correct Direct Thermal and Thermal Transfer options are now displayed for the following printer models: <ul style="list-style-type: none"> GC420t ZPL GK888t ZPL LP2844 GX420s EPL GX420s HC100 Added the following printer models: <ul style="list-style-type: none"> iMZ220 ZPL iMZ320 ZPL
11 Jun 2013	2.6.77.19	<p>Update Release</p> <ul style="list-style-type: none"> Added the following printer models: <ul style="list-style-type: none"> ZD500R-203dpi ZPL ZD500R-300dpi ZPL
10 Oct 2013	2.7.03.12	<p>Update Release</p> <ul style="list-style-type: none"> Server 2012 is now supported. Users can now change languages settings if they have admin rights (applies to Windows 8 and Server 2012). Corrected an issue where Microsoft Access was reporting incorrect paper names when custom stocks were defined in the driver. User entered values are now validated against the fields range values. Corrected an issue in the ZM400 EPL driver that caused incorrect print positioning and font size printing.

		<ul style="list-style-type: none"> • Corrected the maximum print width for the EZ320, MZ320 and iMZ320 printers. • Added the following printer models: <ul style="list-style-type: none"> ◦ ZE500R Series
07 Feb 2014	2.7.03.16	<p>Update Release</p> <ul style="list-style-type: none"> • Added the following printer models: <ul style="list-style-type: none"> ◦ ZD500 ◦ ZT410 ◦ ZT410R ◦ ZT420 ◦ ZT420R • Removed the following printer models that have past their Service & Support discontinuation date: <ul style="list-style-type: none"> ◦ 110 PAX3 ◦ 170 PAX3 ◦ 140 XiIII ◦ 170 XiIII ◦ 220 XiIII ◦ 2746e ◦ 90 XiIII ◦ 90 XiIII Plus ◦ 96 XiIII ◦ 96 XiIII Plus ◦ DA402 ◦ LP2824-Z ◦ R110 XiIII Plus ◦ R402 ◦ R4Mplus ◦ S400 ◦ S600 ◦ TA402 ◦ TLP2824-Z ◦ Z4M ◦ Z4Mplus ◦ Z6M ◦ Z6Mplus
24 Sep 2014	5.1.07.5146	<p>Update Release</p>

- Corrected an issue where some labels in a batch did not print when printing via a network using the ZDesigner port monitor.
- Improved throughput performance when using USB and Link-OS printers.
- To improve throughput performance the 'Use ZIP Compression' setting is now enabled by default in all ZPL models.
- Corrected an issue where the spooler could resend firmware to the printer more than once during a firmware update.
- Corrected an issue where the driver was not installed in the selected language in the installation wizard.
- Corrected the maximum print speed settings for the ZT410 and ZT420 printers.
- Corrected the minimum label length for the ZT410 and ZT420 printers.
- The RFID option in the ZT410R and ZT420R is now enabled.
- Corrected an issue where no memory slot was available for selection in the Font Downloader when using ZD500, ZT410 or ZT420 printers.
- The PrnList.txt file has been removed from the distribution.
- Corrected the maximum print width in G-Series EPL and ZT-Series EPL drivers.
- To simplify Plug 'n' Play installations, the driver distribution now has a method to prepare the computer system by adding the driver to the computer's driver store.
- Microsoft has ended support for Windows XP (<https://windows.microsoft.com/en-us/windows/end-support-help>). This driver release aligns to that decision, with support for Windows XP having been removed. The prior version, 2.7.03.16, does support Windows XP and shall remain available on our website for download for an extended period of time. Version 2.7.03.16 is available 'as is'.
- There is nothing implemented to prevent this driver from running on Windows XP. However, this and future versions are not tested on Windows XP.
- Added the following printer models:
 - ZQ510
 - ZQ520

		<ul style="list-style-type: none"> ◦ GT800 (300dpi)
06 Mar 2015	5.1.07.5675	<p>Update Release</p> <ul style="list-style-type: none"> • The user interface for the ZD500 300dpi EPL driver has been corrected and now shows EPL options. • Corrected center/left aligned print positioning on ZD500 203dpi EPL and ZT410 203dpi EPL drivers when printing less than full width. • Corrected an issue when using ZebraDesigner Pro and printing a one digit Code 39 barcode. • Changed the maximum print quantity from 32000 to 99999999 when printing from applications such as ZebraDesigner. Maximum print quantity is still 32768 when using applications such as Word due to Windows signed integer limitation. • Improvements to the printer installation wizard including a feature to remove previously installed drivers from the driver store. • Drivers installed using the printer installation wizard can now be removed using the Print Management console. • Added the following printer models: <ul style="list-style-type: none"> ◦ ZD410 ◦ ZD420 ◦ ZR338 ◦ ZR628 ◦ ZR638 ◦ ZT410R 600dpi
06 Aug 2015	5.1.07.5682	<p>Update Release</p> <ul style="list-style-type: none"> • This release has been certified for Windows 10. • Improvements to the printer installation wizard - previously it could remove all printers and related drivers. It can now optionally remove drivers even if there is no related printer installed. • The about dialog graphic has been updated to reflect new branding.

		<ul style="list-style-type: none"> • Support for the ^RL RFID command is supported for use with ZebraDesigner. • The help file has been updated with the new corporate address and references removed to operating systems no longer supported. • Corrected print speed limits in ZD500 and ZT410 EPL drivers. • Corrected an issue in the Font & Graphic Downloader where it generated the same file name for different size fonts. • Microsoft has ended extended support for Windows Server 2003. This driver release aligns to that decision, with support for Windows Server 2003 having been removed. The prior version, 2.7.03.16, does support Windows Server 2003 and shall remain available on our website for download for an extended period of time. Version 2.7.03.16 is available 'as is'. • There is nothing implemented to prevent this driver from running on Windows Server 2003. However, this and future versions are not tested on Windows Server 2003.
26 Feb 2016	5.1.07.6290	<p>Update Release</p> <ul style="list-style-type: none"> • The Status Monitor installer now includes Zebra's digital signature. • Corrected an issue where the existence of the zebrazbrn.inf could cause USB installation issues. The installer now checks for it and deletes it if necessary. • Implemented support for RFID EPC Gen2 v2. This adds a new PC Word data field in ZebraDesigner where the user can set the PC Word. • For RFID 240bit EPC tag, 7800 is now sent for PC Memory instead of 6000. • Corrected an issue where RFID user data was incorrectly written to the EPC memory field.
07 Sep 2016	5.1.16.6447	<p>Update Release</p> <ul style="list-style-type: none"> • Updated the EULA in the distribution. • Corrected an issue where a tilde character was not encoded correctly in a Datamatrix barcode.

		<ul style="list-style-type: none"> • Updated Japanese translations in the UI for ZPL printers. • For CPCL printers the FORM command is no longer sent when the paper type is set to Journal. • A new RTC format is supported when using ZebraDesigner (YYJJ: year in two digits + julian date). • Corrected an issue where the about dialog displayed garbage if the model name was greater than 32 characters. • The driver is now Package-aware to support the Microsoft security update described in Article ID: 3170005 • Added the following printer models: <ul style="list-style-type: none"> ◦ ZQ310 ◦ ZQ320 ◦ ZT510 ◦ ZT610 ◦ ZT610R ◦ ZT620 ◦ ZT620R ◦ ZR318 ◦ ZR328
13 Feb 2017	5.1.16.6465	<p>Update Release</p> <ul style="list-style-type: none"> • Corrected an issue where Zebra Setup Utilities may stop responding on Windows 10 after the printer connected via USB had restarted. • Added the following printer models: <ul style="list-style-type: none"> ◦ ZD620
16 Oct 2017	5.1.16.6839	<p>Update Release</p> <ul style="list-style-type: none"> • This release includes certification for Windows Server 2016. • Added Linerless Peel, Linerless Cut and Linerless Delayed Cut modes to support ZD600 series. • Using up/down arrows to set number of copies now works correctly when using Microsoft applications.

		<ul style="list-style-type: none"> • Corrected RFID tag options for the ZT600R series. • Corrected an issue where an error occurred in ZebraDesigner when selecting tag data for an EPC Class 0 64/96 bit RFID tag. • Added the following printer models: <ul style="list-style-type: none"> ◦ GK420E ◦ GK888E
01 Nov 2017	5.1.16.6846	Update Release <ul style="list-style-type: none"> • Changed the GK420E/GK888E PnP strings to GK420e/GK888e.
05 Dec 2017	5.1.16.6849	Update Release <ul style="list-style-type: none"> • Added the following printer models: <ul style="list-style-type: none"> ◦ GK420t Plus ◦ ZD510 ◦ ZQ610 ◦ ZQ620 ◦ ZR658 ◦ ZR668
23 Mar 2018	5.1.16.6854	Update Release <ul style="list-style-type: none"> • Added the following printer model: <ul style="list-style-type: none"> ◦ GT800 Plus
18 Jun 2018	5.1.16.6857	Update Release <ul style="list-style-type: none"> • Added the following printer models: <ul style="list-style-type: none"> ◦ ZD511 ◦ ZQ120 ◦ ZQ220 ◦ ZQ630 ◦ ZQ630R ◦ ZR138
15 Aug 2018	5.1.16.6917	Update Release <ul style="list-style-type: none"> • Corrected an issue where the wrong version number was displayed in the about dialog.

		<ul style="list-style-type: none"> • Corrected an issue in the ZT620 driver that prevented memory card options displaying in the Font & Graphic downloader. • Added the zebra.com url in the ZD620 about dialog. • Updated some configuration files for consistency.
06 Sep 2018	5.1.16.6924	<p>Update Release</p> <ul style="list-style-type: none"> • Added the following printer models: <ul style="list-style-type: none"> ◦ ZD220 ◦ ZD230 ◦ ZD888
04 Jan 2019	5.1.16.6927	<p>Update Release</p> <ul style="list-style-type: none"> • Microsoft has ended support for Windows Vista (https://support.microsoft.com/en-gb/help/22882/windows-vista-end-of-support). This driver release aligns to that decision, with support for Windows Vista having been removed. • Added the following printer models: <ul style="list-style-type: none"> ◦ ZT411 ◦ ZT411R ◦ ZT421 ◦ ZT421R
18 Jun 2018	5.1.16.7110	<p>Update Release</p> <ul style="list-style-type: none"> • Corrected the ZR668 model description from CPLC to CPCL. (PnP was not affected) • Corrected the maximum media width for the ZD500R 300dpi model. • Corrected the default darkness setting for the ZR628 and ZR638 ZPL drivers. Changed from 0 to 10. • Corrected the minimum height and width for the ZQ310, ZQ510 and ZR318. • Added the following printer models: <ul style="list-style-type: none"> ◦ ZQ112 ◦ ZQ210 ◦ ZQ511 ◦ ZQ511R

		<ul style="list-style-type: none"> ◦ ZQ521 ◦ ZQ521R ◦ ZR118
21 Aug 2019	5.1.16.7117	<p>Update Release</p> <ul style="list-style-type: none"> • This release has been certified for Windows Server 2019.
10 Feb 2020	5.1.16.7217	<p>Update Release</p> <ul style="list-style-type: none"> • The Direct Thermal and Thermal Transfer options are now selectable in the ZD888 and ZD220 drivers. • Corrected an issue in the Font & Graphic downloader that caused text to be mis-aligned when downloading and using a rotated font in CPCL. • Added the following printer models: <ul style="list-style-type: none"> ◦ ZD411 ◦ ZD421 ◦ ZD611 ◦ ZD611R ◦ ZD621 ◦ ZD621R
28 Jul 2020	5.1.16.7228	<p>Update Release</p> <ul style="list-style-type: none"> • Added the following printer models: <ul style="list-style-type: none"> ◦ ZE511 ◦ ZE511R ◦ ZE521 ◦ ZE521R
22 Jan 2021	5.1.16.7398	<p>Update Release</p> <ul style="list-style-type: none"> • Added the following printer model: <ul style="list-style-type: none"> ◦ ZD421CN
14 Mar 2022	5.1.17.7407	<p>Update Release</p> <ul style="list-style-type: none"> • Microsoft have changed the requirements and driver certification process to align with operating systems they currently support. In

		<p>line with that change, this driver shall no longer be tested on, or certified for Windows 7, Windows 8.1 or Windows Server 2012.</p> <ul style="list-style-type: none"> • The driver certification now includes Windows 11 and Windows Server 2022. • The Status Monitor now correctly reports status of the KR403. • The Status Monitor no longer displays ZSB printers. • The minimum label length/height has been corrected for the ZD420/421, ZD620/621 and ZT610/620 models. <ul style="list-style-type: none"> ◦ Note: the minimum value applies to the operation mode with the shortest supported label length. Other operation modes may have a different minimum length. • The speed settings have been corrected for the ZD220 and ZD230 models. • Added the following printer models: <ul style="list-style-type: none"> ◦ ZT111 ◦ ZT211 ◦ ZT231 ◦ ZT231R
9 Aug 2022	5.1.17.7412	<p>Update Release</p> <ul style="list-style-type: none"> • Added the following printer models: <ul style="list-style-type: none"> ◦ ZQ120 Plus ◦ ZQ220 Plus ◦ ZQ310 Plus ◦ ZQ320 Plus ◦ ZQ610 Plus ◦ ZQ620 Plus ◦ ZQ630 Plus ◦ ZQ630R Plus ◦ ZR328 Plus ◦ ZR668 Plus

[Back to top](#)

Technical Support

Worldwide Technical Support is available through your Reseller, or at:

<https://www.zebra.com/contact>

Zebra Technologies Corporation
Corporate & International Headquarters
3 Overlook Point
Lincolnshire, Illinois 60069 USA
Phone: +1 847 913 2259
Fax: +1 847 913 2578

[Back to top](#)

Software Updates

Updated ZDesigner drivers will be available on our web site:
<https://www.zebra.com/support>

[Back to top](#)

©2022 Zebra Technologies Corporation and/or its affiliates. All rights reserved.