

MZ Firmware Release Notes

This document summarizes the following firmware releases:

Firmware Release Number	Release Date	See Page
11z48	04 October 2011	page 2
11z29	28 July 2010	page 3
11q4	09 May 2008	page 3
11m8	08 April 2008	page 4
10t	14 August 2007	page 5
04u023	26 February 2007	page 6
04u019	04 December 2006	page 6
04u016	26 October 2006	page 6

Hardware Requirements:

This firmware requires one of the following Zebra Mobile Printers:

Note that firmware releases prior to 11z48 will not run on the M2F-XXXXXXXXXX or M3F-XXXXXXXXXX platforms.

Firmware Releases:

11z48

Release Date: 04 October 2011

Enhancements

- Add support for the M2F and M3F platforms
- Add support for datamatrix barcodes to MZ printers [7630]
- WLAN: Added SHA2 support for PEAP authentication [7875]
- WLAN: Removed VPN firmware [4948]
- WLAN: Add EAP session resumption (see below for description) [6958]

Issues Corrected

- Multiple enabled Avalanche auto-run packages will not update correctly [6868]
- Avalanche custom properties not working correctly [6721]
- MZ's improperly printing text messages from the Avalanche server [6211]
- Print.tone SGD parameter does not handle values about 127 [7335]
- WLAN: PEAP auth unsuccessful due to unsupported certificate fields [7940]
- WLAN: EAP-FAST failing on ACS 5.1 [8010]
- WLAN; User was allowed to turn the unsupported 802.11d feature on which resulted in wireless communication interruptions [5146]
- Incorrect Top-Of-Form registration on the MZ [8035]

EAP Session Resumption

Benefit: Enables faster roaming when using EAP-based protocols

Summary: After a printer and the network have previously negotiated an EAP session, and due to roaming or falling out of range and returning into range, begin a new EAP negotiation, they can agree to resume the previous session. This significantly reduces the time required to establish the new session from tens of seconds to seconds. In order for this to work, EAP Session Resumption must be enabled in the network infrastructure equipment by the network administrator. EAP Session Resumption is automatically supported in the printer when using any EAP-based protocols such as PEAP, LEAP, EAP-TLS, EAP-TTLS, or EAP-FAST. No printer configuration changes are required.

11z29

Release Date: 28 July 2010

Enhancements

None

Issues Corrected

- CPCL: Resident font corruption after print line using scalable font [3302].
- CPCL: Change default media mode to journal [3487].
- CPCL: Vietnamese fonts not printing correctly [5980].
- BT: Encryption not indicated properly in 2-key report when Bluetooth authentication is enabled [0640].
- BT: Problems printing from Cipher Labs terminal [3416].
- BT: Partial print failures using Bluetooth [4928].
- BT: Not responding to query over Bluetooth [5731].
- 802.11: Change default wlan.keep_alive value to "ON".
- 802.11: Unable to perform EAP-FAST authentication with Cisco 2106 [3669].
- 802.11: Not properly responding to duplicate SYN's [6373].
- 802.11: Radio can occasionally lock up [4776] [5442].
- 802.11: Improper TCP handshake, occasionally not setting SYN flag in acknowledgement packets [5258].
- 802.11: Authentication failed with PEAP on IAS2008 server [5620].
- 802.11: Change default roam packet setting to "ON" [3488].

11q4

Release Date: 09 May 2008

Enhancements

• Update to handle 2048 byte keys and to check for duplicate EAP identifier numbers.

Issues Corrected

- Enhanced signal strength, roaming support, and power save responsiveness for the Zebra 802.11g radio.
- Fixed conflict with IrDA and Bluetooth residing in the same printer.

Additional information regarding the improvements to the Zebra 802.11g radio:

This software release improves the internal signal strength reporting for the Zebra 802.11g radio. These enhancements improve the printer's operation in areas with weak signals. As a result of these changes the printer should roam less frequently.

Additionally, changes to the radio's power-save algorithm have been made which will also result in improved performance. Note that the power-save behavior is affectd by settings on both the access point and the printer. In particular, it should be noted that access point settings have a direct relationship on wireless device sleep periods.

11m8

Release Date: 08 April 2008

Enhancements

- Added paper sensor support.
- Added roam logging for G radio.
- Added event logging.
- Added roam logging when failed to query radio for signal strength.
- Added Bluetooth connection shutdown when "device.reset" is issued.
- (EAP-TLS): Update for determining TLV PEAP package in tunnel.
- Added sync function to the Bluetooth Stack. This function sends a known command to the Bluetooth radio and waits for a proper response. It will try 10 times (1 second) in order to identify when the radio is in a ready state.
- Enable bar sensor information on the two-key report.
- Support common motor driver.
- (Avalanche) AMC 4.4 support added.

Issues Corrected

- (Bluetooth 2.0): Update for display of "auto" in bluetooth.radio_auto_baud field and setting of 57 baud in NVM, BT app download now works with 2.0 radios.
- (Bluetooth 2.0): Removed credit limit.
- Reset BT priority and setup hardware handshaking if BT hardware is present.
- (WPA2): Fixed issue with connecting to Cisco WLAN Controller Network.
- Addressed noisy printing with new sensors.
- Fixed line printing for receipt exceeding 161 inches.
- Removed forced printing of the line print buffer when the printer receives a Bluetooth disconnect complete event.

10t

Release Date: 14 August 2007

Enhancements

- (EAP-TLS): Added logic to prevent repeated PAP challenge responses.
- (EAP-TLS): Update to work with SBR server. The SBR was suggesting TTLS for inner authentication, this is now NAK'd. The update will now NAK all inner requests besides MSCHAPv2.
- (Avalanche): Changes made to _devprop.prf file e.const part. for each property starts on the new line.
- Added support for turning on the option for sending an IP packet when roaming.
- Changed TCP socket behavior so a duplication connection does not immediately disconnect the previous connection. It will only happen after 30 seconds.
- (WPA): EAPOL START is sent if AP does not start EAP handshake within 5 seconds after association.
- WPA2 Broadcast key rotation for both AES and TKIP.
- Added support for wlan.wpa.wpa_version, wlan.wpa.groupkey_ciphersuite, and wlan.wpa.pairwise ciphersuite.
- Changed the interrupt priority of the Bluetooth port.
- New chip replacing an obsoleted chip on the IrDA module board required software changes.
- Made required changes for the new IrDA chip.
- Added IrDA input source which fixes line print mode behavior when using IrDA.
- Fixed font numbering issue which was causing font 2 to not print.
- (Avalanche): Increased number of allowable properties to 128.
- Now ignores the inactivity timeout when charging.
- Now allows printing when in charging bay.
- (Bluetooth 2.0): Added ability to download the printer application via Bluetooth.
- New G radio firmware: FW image 5.02.14.

Issues Corrected

- (Avalanche): Fixing buffer overflow that will prevent unit from resetting.
- (Avalanche): Corrected UDP malformed packets.

04u023

Release Date: 26 February 2007

Enhancements

- Added changed roaming scan behavior for G radio so only one channel is scanned per 100ms interval. This allows the radio to be more responsive to normal traffic while in a roaming state.
- (G radio): Added user configurable parameter for roam signal and interval.
- Changed the default print speed to 3.
- Enable Vietnamese Encoding.

Issues Corrected

• Corrected problem with G radio when losing association while roaming. Radio would not re-associate.

04u019

Release Date: 04 December 2006

Enhancements

- Improve power save and roaming behavior with Samsung radio.
 - Added function to select strongest Unicast cipher for WPA2 if AP has more than one Unicast cipher enabled.
 - POP3 enhancements to handle out-of-paper and HTML text-encoding not being printed.

Issues Corrected

• n/a

04u016

Release Date: 10 October 2006

Enhancements

• Original release

Issues Corrected

• n/a