

# QL Plus and RW Summary of Firmware Changes

This document summarizes the following QL Plus and RW firmware releases:

Firmware Release Number	Release Date	See Page
11p10	7 May 2008	page 1
10z	3 October 2007	page 2
10m	02 July 2007	page 3
10g	23 April 2007	page 4
04u17-5	24 January 2007	page 5
04u17-3	12 December 2006	page 6
04u17	3 November 2006	page 6

# 11p10

Release Date: 7 May 2008

This firmware release includes all features of previous base version 10z (see page 2), except for the EPL and APL-I emulations. Customers who need these features should **not** use this version of the firmware.

It is for use with the following printer models:

- RW 420 (R4A-XXXXXXXXXXXXXX)
- RW 220 (R2A-XXXXXXXXXXXXX)



**Note** • This firmware does <u>not</u> run on the older QL (H8 based) series printers (QXA-XXXXXXXX-XX or QXB-XXXXXXXXXX).

# **Changes**

- Bluetooth 2.0: Improved BT throughput on the RW by removing credit limits.
- Added support for the Secure File Transfer Protocol (SFTP) for use with mirror, see below for instructions.
- Added support to shutdown active Bluetooth connection when "device.reset" command is issued.
- · Added Event and roam logging
- Netmanage: Added AMC 4.4 support

• Update to handle 2048 byte keys and to check for duplicate EAP identifier numbers

### Instructions for using Secure FTP with mirror:

To use SFTP during mirror, use the SGD command ip.mirror.mode and set the parameter value to sftp.



**Note** • The parameter value can be either ftp or sftp, with the default being ftp.

### **Issues Corrected**

- ZPL: fixed ID Matrix barcode.
- Fixed line printing for receipts exceeding 161 inches
- Enhanced signal strength, roaming support, and power save responsiveness for the Zebra value 802.11g radio.

Additional information regarding the improvements to the Zebra 802.11g radio:

This software release improves the internal signal strength reporting for the Zebra 802.11g radio. These enhancements improve the printer's operation in areas with weak signals. As a result of these changes the printer should roam less frequently.

Additionally, changes to the radio's power-save algorithm have been made which will also result in improved performance. Note that the power-save behavior is affected by settings on both the access point and the printer. In particular, it should be noted that access point settings have a direct relationship on wireless device sleep periods.

### 10z

#### Release Date: 3 October 2007

This firmware release includes all features of previous base version 10m (see page 3). It is for use with the following printer models:

- RW 420 (R4A-XXXXXXXXXXXX)
- RW 220 (R2A-XXXXXXXXXXXX)



**Note** • This firmware does <u>not</u> run on the older QL (H8 based) series printers (QXA-XXXXXXXX-XX or QXB-XXXXXXXXXX).

14587L-002 08/19/2008

### **Changes**

- Added ability to download applications via Bluetooth.
- On the LCD, the arrow icon now blinks for data transmission instead of the light icon
- Update for determining TLV PEAP package in tunnel
- · Added roam logging for G radio

#### Issues Corrected

• (WPA2): Fixed issue with connecting to Cisco WLAN Controller Network

### 10m

#### Release Date: 02 July 2007

This firmware release includes all features of previous base version 10g (see page 4). It is for use with the following printer models:

- RW 420 (R4A-XXXXXXXXXXXX)



**Note** • This firmware does **not** run on the older QL (H8 based) series printers (QXA-XXXXXXXXXXX or QXB-XXXXXXXXXX).

# **Changes**

- Added Support for IPL
- Made required changes for the new IrDA chip
- Added ability to return the Magnetic Card Reader data of previous swipe
- (Avalanche): Increased the number of available properties to 128
- (ZPL emulation):
  - ^HH command uploads ZPL config settings
  - Added SGD ZPL commands:
  - zpl.calibrate calibrates printer (same as ^JC)
  - zpl.save saves ZPL settings
  - ZPL two-key changes:
  - Remove actual Label Length
  - Added Print Width

### **Issues Corrected**

• Fixed font numbering issue which was causing font 2 to not print.

08/19/2008 14587L-002

### 10g

#### Release Date: 23 April 2007

This firmware release includes all features of previous base version *04u17-5* (see page 5). It is for use with the following printer models:

- RW 420 (R4A-XXXXXXXXXXXX)
- RW 220 (R2A-XXXXXXXXXXXX)



**Note** • This firmware does <u>not</u> run on the older QL (H8 based) series printers (QXA-XXXXXXXX-XX or QXB-XXXXXXXXXX).

### **Changes**

- (EAP-TLS): Added logic to prevent repeated PAP challenge responses
- (EAP-TLS): Update to work with SBR server. The SBR was suggesting TTLS for inner authentication; this is now NAK'd. The update will now NAK all inner requests besides MSCHAPv2.
- Version 4.07 -- Added VERBOSE option to Magnetic Card Reader (MCR)
- POP3 enhancements to handle out-of-paper and HTML text-encoding (don't print it)
- (WPA): Symbol radio now uses 16-bit writes when writing the MIC
- Added support for turning on the option for sending an IP packet when roaming
- Changed TCP socket behavior so a duplication connection does not immediately disconnect the previous connection. It will only happen after 30 seconds
- WPA2 Broadcast key rotation for both AES and TKIP
- (MCR): Version 4.08 -- Added setvar "mcr.out". This setvar command will be used to send MCR data from the printer to a particular destination either by TCP, SRF, or SERIAL
- · Changed the interrupt priority of the Bluetooth port
- (ZPL): UPC/EAN barcodes: initialized mode to 1 in parse function so interpretive field prints correctly -- first character outside of barcode
- (IRDA): New chip replacing an obsoleted chip on the IrDA module board, required software changes
- (NetManage): Support saving GUID into non volatile memory
- (WPA): Added support for wlan.wpa.wpa\_version, wlan.wpa.groupkey\_ciphersuite, and wlan.wpa.pairwise\_ciphersuite

### **Issues Corrected**

• (ZPL): recalling formats from flash containing barcode fields -- no data was being included in barcode

14587L-002 08/19/2008

### 04u17-5

### Release Date: 24 January 2007

This firmware release includes all features of previous base version 04u17-3 (see page 6). It is for use with the following printer models:

- RW 420 (R4A-XXXXXXXXXXXX)
- RW 220 (R2A-XXXXXXXXXXXX)



Note • This firmware does <u>not</u> run on the older QL (H8 based) series printers (QXA-XXXXXXXXXX or QXB-XXXXXXXXXX).

### **Changes**

- (Avalanche): Changes made to \_devprop.prf file e.const part of each property starts on the new line.
- (WPA): EAPOL START is sent if AP does not start EAP handshake within 5 seconds after association

### **Issues Corrected**

- (Avalanche): Fixed buffer overflow that prevented unit from resetting
- (Avalanche): Corrected UDP malformed packets.

08/19/2008 14587L-002

### 04u17-3

#### Release Date: 12 December 2006

This firmware release includes all features of previous base version 04u17 (see page 6). It is for use with the following printer models:

- RW 420 (R4A-XXXXXXXXXXXXX)
- RW 220 (R2A-XXXXXXXXXXXXX)



**Note** • This firmware does <u>not</u> run on the older QL (H8 based) series printers (QXA-XXXXXXXX-XX or QXB-XXXXXXXXXX).

## **Changes**

• 80211g radio: Added user configurable parameter for roam signal and interval

### **Issues Corrected**

n/a

### 04u17

#### Release Date: 3 November 2006

This firmware release is for use with the following printer models:

- RW 420 (R4A-XXXXXXXXXXXXX)
- RW 220 (R2A-XXXXXXXXXXXX)



**Note** • This firmware does <u>not</u> run on the older QL (H8 based) series printers (QXA-XXXXXXXX-XX or QXB-XXXXXXXXXX).

# Changes

- New Symbol Radio Firmware 3.91-80
- Changed wlan.keep\_alive.enable default to be OFF
- Improved PowerSave and Roaming with the 80211g radio

### **Issues Corrected**

• n/a

14587L-002 08/19/2008