

RFD8500 SAACPS00-006-R71 Release Notes

This document summarizes the following firmware releases:

Firmware Release Number	Release Date	See page
SAACPS00-006-R71	02-November-2020	Page 1

For support, please visit www.zebra.com/support

RFD8500 Version SAACPS00-006-R71

RELEASE DATE: 02-November-2020

This release notes is for the RFD8500 maintenance release SAACPS00-006-R71.

RFD8500 software is available by updating 123Scan latest plugin.

The plugin name for this release is RFD8500-COMMON_MODELS-S-071.SCNPLG.

Contents of the release package:

IMAGE TYPE	VERSION	FILE NAME
Super combined RFD8500 image	SAACPS00-006-R71	SAACPS00-006-R71D0.DAT
NGE FW	1.4.86	nge-bf525-dev-rev1.4.86.DAT
RFD8500 123Scan plug-in		RFD8500-COMMON_MODELS-S-071.SCNPLG
iPL3307 123Scan plug-in		IPL3307-RFD8500_MODELS-S-005.SCNPLG
RFID Demo App for Android	1.0.2.17	Zebra_RFID_Mobile_Android_1.0.2.17.zip
RFID SDK for Android	2.0.1.34	Zebra_RFIDAPI3_SDK_2.0.1.34.zip
Zebra 123RFID Mobile	1.0.0.45	123RFID_Mobile_1.0.0.45.zip
Zebra RFID SDK for iOS	1.1.0	Zebra_RFID_SDK_1_1_0.pkg
RFID iOS Demo App	1.1.0	RFIDDemoApp_1_1_0.adhoc.ipa

RFID SDK for Windows	2.1.9	Windows.Mobile.SDK_v2.1.9.zip Windows.Desktop.SDK_v2.1.9.zip
RFID Windows Demo App	2.1.9	Windows.Desktop.DemoApp_v2.1.9.zip Windows.Mobile.DemoApp_v2.1.9.zip
RFID SDK for Xamarin (Android)	2.0.1.34	Zebra_RFIDAPI3_XAMARIN_SDK_2.0.1 .34.zip

- **All the SDK's and Demo Apps are available in Zebra support site @ <https://www.zebra.com/us/en/support-downloads/rfid/rfid-handhelds/rfd-8500.html>**

HARDWARE REQUIREMENTS

- RFD8500 All SKUs
- RFD8500 Thailand SKU

ENHANCEMENTS / CHANGES in SAACPS00-006-R71 with respect to SAACPS00-006-R69

- Added Thailand SKU, with following region configuration.
Channel list: 921250,921750,924250,923750,920750,922250,923250,922750
Max power is set to **300** dBm
Default power is set to **270** dBm
- Modified Indonesia, with following (Randomized) channel list
Channel list: 924750, 923750, 924250, 923250
- Enhanced Logging Feature.
NGE packet log: Fixed truncated packet logging.
- Added NGE version 1.4.86
Fix for FM0-640 hang-up issue
Fix for Forward Power Low Alarm
- Following issues have been fixed in this release
 - Device doesn't update power level while charging until reader is taken out of cradle when reader is placed in cradle the second time.
 - When the device is placed in cradle second time reader, battery level is not updated to charging or discharging.

ADDITIONAL NOTES

Summary of major issues and limitations are listed below.

- The RFD8500 RFID region should be configured first before using any RFID functions. The region can be configured via RFID demo apps or ZETI interface. Refer to the RFD8500 user guide and the developer guide for more details. If not familiar with region configuration, it is recommended to set region configuration using the RFID demo apps or the ZETI interface instead of 123Scan.
- When in HID mode, a beep sequence is heard if the region is not set and the trigger is pressed.
- The RFD8500 works in two main modes over Bluetooth: HID mode, SPP and MFi combo mode, which is the default. Combo mode allows the RFD8500 to be paired with either iOS or Android devices out of the box. To enable Bluetooth HID the RFD8500 123Scan plug-in should be used. The setting HID keyboard emulation profile should be chosen under General->Bluetooth->Bluetooth Profile Mode.
- The RFD8500 Bluetooth is discoverable for 40 seconds (by default or as per the configured value) each time it becomes discoverable, the RFD8500 trigger button must be pressed within 25 seconds to accept the pairing request once RFD8500 starts flashing Bluetooth LED fast. It is recommended to use MC40 with Android KK version 4.4.4 & Android L 5.1.1, TC55 Android version 4.4.3, TC70 with Android L Version 5.1.1 and TC51 with Android M Version 6.0.1. Android 4.4.3 is the minimum requirement for RFID demo app.
- Batched data can get lost when unit goes to off mode after 30 minutes of inactivity. Batched data should be offloaded within this time windows.
- When 123Scan is used to configure the RFD8500, the RFD8500 should be power cycled to complete the configuration process.
- RFD8500 does not support setting configuration via barcode scanning.

KNOWN ISSUES

- ZETI password is not configurable via 123Scan. Use the ZETI interface directly to configure it
- Sometimes during inventory with C1G2 Session 1/ 2/3 behavior resembling Session 0 is seen with Higgs 3 based tags.
- After sending Switch host from USB CDC to SNAPI the USB cable needs to be removed and connected back for this to take effect.
- Configuring HID on either of the interfaces (USB or BT) causes the other interface to acquire the HID characteristics for RFID. It is not recommended usage of device using HID on one interface and using ZETI based RFID on the other interface.
- Sometimes RFD8500 may not transition to off mode after being idle for 30 minutes when used in BT HID mode and with an iOS v8.4.1 host. To reduce the probability of this event, it is recommended to configure parameter 1633 to a value much less than default value, 1800 seconds (30 minutes), such as 300 seconds (5 minutes)
- In RFID demo app for Android v1.0.2.x read rate is updated in inventory page when data is retrieved in batch mode (read rate should not be in batch mode)
- Intermittent issue seen with iOS 10 when sometimes the RFID demo app does list all connected devices
- The addition of the NAK has caused a performance degradation of about 3% in FM0/640 compared to previous version (1.8.R00)

- When RFD8500 is rebooted several times when connected to the iPhone BT auto reconnection fails on few occasions.