Release Notes - MC67NA JB - BSP v030515 - Hotfix CFE v01.06.00 package

Introduction Description

Package Details

Device Compatibility Installation Requirements

Installation Instructions

Introduction

HotFix CFE (Cumulative Fixes from Engineering) Package includes multiple SPR Hotfixes contained into a single package. The HotFix CFE Package helps the end users to keep up to date with all the SPR hotfixes for given product software

HotFix CFE packages are validated only by engineering validation team and the package follows Zebra Technologies HotFix Package Policy. Click here to view HotFix Package Policy. HotFix Support Policy

Description

 $The \ content \ and \ related \ Hot \ fixes \ that \ are \ included \ in \ this \ Hot Fix \ CFE_MC67NA_JB_030515_EN_v010600. zip \ \ is \ as \ follows.$

SPR No	Synopsis	
28631	Keyboard Repeating Key Issue.	
27006	GPS stops reporting Fix, after the service thread leak.	
28252	UAF kernel patch	
28147	Android Stagefright patch	
27339	Screen is unable to rotate on all four sides	
27892	AOSP browser fails to capture function keys	
	Disable low temperature warning pop up dialog when temperature lower than -15 degrees. Fix Ethernet should not be reconnected when its state is linked down.	

Package Details

CFE_MC67NA_JB_030515_EN_v010600.zip

Device Compatibility

This HotFix CFE Package software release has been approved for use with the following Zebra devices.

Device	Operating System	BSP Version
MC67 NA	Android JB 4.1.1	v030515

Installation Requirements

This SW is intended for the MC67NA device running on 01-4AJ11-J-2200-0001-00-M1-030515 build only.

Installation Instructions

- $1. \ Copy \ update \ CFE_MC67NA_JB_030515_EN_v010600. zip \ to \ the \ root \ directory \ of \ SD \ card. The property of \ Card. The property of \ SD \ card. The property of \ SD \ card.$
- 2. Place the SD card in the device to be upgraded and connect to A/C power.
- 3. Press and hold the Power button on the device until the Device options menu appears
- 4. Tap on Reset to reboot the device.
- 5. When the device is rebooting hold the right Action button to enter Recovery update mode.
- 6. When the Recovery Mode screen appears release the Right Action button.
- 7. Tap Home Key to access recovery menu screen.
- 8. Tap Vol+, Vol- keys to navigate to apply update from /sdcard option.
- 9. Tap Enter to select this option.
- 10. Tap Vol+, Vol- keys to navigate to the update zip file.
- 11. Tap Enter to select this option.
- 12. After pressing Enter, the upgrade will start.
- 13. After upgrading successfully, the screen will back to Recovery mode menu.
- 14. Tap Vol+, Vol- keys to navigate to the reboot system now option.
- 15. Tap Enter to select this option.
- 16. After pressing Enter system will reboot.

Release Date

January, 2016