

# Release Notes - MC67NA JB - BSP v030515 - HotFix CFE v00.04 package

- [Introduction](#)
- [Description](#)
- [Package Details](#)
- [Device Compatibility](#)
- [Installation Requirements](#)
- [Installation Instructions](#)
- [Release Date](#)

## Introduction

HotFix CFE (Cumulative Fixes from Engineering) Package includes multiple SPR Hotfixes contained into a single package. The HotFix CFE Package helps the end users to keep up to date with all the SPR hotfixes for given product software release / revision.

HotFix CFE packages are validated only by engineering validation team and the package follows Zebra Technologies HotFix Package Policy. Click here to view HotFix Package Policy.[HotFix Support Policy](#)

## Description

The content and related Hot fixes that are included in this HotFix CFE-MC67NA-J-F0-030515-x-00-04.zip is as follows.

SPR No	Synopsis
29248	Keyboard not responding
28631	Keyboard Repeating Key Issue.
27006	GPS stops reporting Fix, after the service thread leak.
28252	UAF kernel patch
28147	Android Stagefright patch
27339	Screen is unable to rotate on all four sides
27892	AOSP browser fails to capture function keys
	<ul style="list-style-type: none"><li>Disable low temperature warning pop up dialog when temperature lower than -15 degrees.</li><li>Fix Ethernet should not be reconnected when its state is linked down.</li></ul>

This HotFix CFE package CFE-MC67NA-J-F0-030515-x-00-04.zip obsoletes the following HotFix CFE:

HotFix CFE version	Product
CFE_MC67NA_JB_030515_EN_v010600.zip	MC67NA
CFE_MC67NA_JB_030515_EN_v010500_e_v1_0.zip	
CFE_MC67NA_JB_030515_EN_v010200_e_v1_0.zip	

**Note:** Latest CFE package includes the previous and new SPR HotFixes.

## Package Details

CFE-MC67NA-J-F0-030515-x-00-04.zip

## Device Compatibility

This HotFix CFE Package software release has been approved for use with the following Zebra devices.

Device	Operating System	BSP Version
MC67 NA	Android JB 4.1.1	v030515

## Installation Requirements

This SW is intended for the MC67NA device running on 01-4AJ11-J-2200-0001-00-M1-030515 build only.

## Installation Instructions

- Copy update CFE-MC67NA-J-F0-030515-x-00-04.zip to the root directory of SD card.
- Place the SD card in the device to be upgraded and connect to A/C power.
- Press and hold the Power button on the device until the Device options menu appears.
- Tap on Reset to reboot the device.
- When the device is rebooting hold the right Action button to enter Recovery update mode.
- When the Recovery Mode screen appears release the Right Action button.
- Tap Home Key to access recovery menu screen.
- Tap Vol+, Vol- keys to navigate to apply update from /sdcard option.
- Tap Enter to select this option.
- Tap Vol+, Vol- keys to navigate to the update zip file.
- Tap Enter to select this option.
- After pressing Enter, the upgrade will start.
- After upgrading successfully, the screen will back to Recovery mode menu.
- Tap Vol+, Vol- keys to navigate to the reboot system now option.
- Tap Enter to select this option.
- After pressing Enter system will reboot.

## Release Date

August, 2016