Release Notes – MC92 CE7.0 – BSP v06.57.22 - Mobicontrol application is not available after cold boot the device – SPR32740

Introduction

Description

Contents

Device Compatibility

Installation Requirements

Installation Instructions

Part Number and Release Date

Introduction

SPR32740 - After cold boot the device, Mobicontrol application is not persistent (no longer available) in startup menu.

Description

Mobicontrol application is not persistent (no longer available) after cold boot the device. To resolve this issue please use

'SPR32740 MC92 C70 en 065722 v1 WB.cab/SPR32740 MC92 C70 en 065722 v1 NB.cab'.

Contents

SPR32740_MC92_C70_en_065722_v1_WB.cab (Hotfix with auto Warm boot) SPR32740_MC92_C70_en_065722_v1_NB.cab (Hotfix without auto Warm boot)

Device Compatibility

This software release has been approved for use with the following Zebra devices,

Device	Operating System	BSP
MC92N0	CE 7.0	v06.57.22

Installation Requirements

MC92N0 device must contain a released version of CE 7.0 with BSP v06.57.22.

Installation Instructions

For Normal installation of the PATCH:

- Copy "SPR32740_MC92_C70_en_065722_v1_WB.cab" file to the application folder on the device by using Microsoft Active Sync or Mobile Device Center.
- 2. Navigate on the device to the application folder.
- 3. Deploy the solution by tapping on the "SPR32740_MC92_C70_en_065722_v1_WB.cab" file.
- 4. After successful deployment of the "SPR32740_MC92_C70_en_065722_v1_WB.cab " file, device will do an automatic warm boot.

For MSP or REMOTE installation of the PATCH:

- Set up MDM (MSP, Soti, Airwatch, etc..) to send
 "SPR32740_MC92_C70_en_065722_v1_NB.cab" file to the application folder of the device.
- 2. To deploy the solution, setup in MDM to install the cab file "SPR32740_MC92_C70_en_065722_v1_NB.cab" file.
- 3. Changes will take effect after a manual reboot of the terminal or if MDM reboots device.

Part Number and Release Date

N/A

September, 2017