Release Notes - Zebra Android Oreo LifeGuard Update 19 Release (NGMS)

Description

Component Contents

Installation Requirements

Installation Instructions

Device Compatibility

Known Issues and Limitations

Description

The details of the Android GMS Oreo LifeGuard release 02-13-15.00-ON-U19-STD that covers family of products including TC5x, TC7x, VC80x, MC33x, MC3300r. Please see, Device Compatibility under Addendum Section for more details.

LifeGuard patches are cumulative and include all previous fixes that are part of earlier patch releases.

Component Contents

Package Name	Package Description
CFE_ATLAS_02-13-15.00-ON-U19-STD.zip	CFE package update

Component Version Info

Component / Description	Version	
Product Build Number	02-13-15.00-ON-U19-STD	
Android Version	8.1.0	
Linux Kernel	3.10.84	

Android SDK Level	27	
Platform	QC8956	
Bluetooth Stack	4.1	
Flash Size	16/32GB	
RAM Size	2/4GB	
Scanning Framework	22.0.6.2	
SimulScan	4.0.5	
SimulScanEngine	3.0.1	
DataWedge	7.3.26	
EMDK	7.3.21.2321	
MXMF / OSX	MXMF: 9.0.4.3 / OSX: QCT.81.8.8.3	
WiFi	FUSION_BA_2_11.1.0.002_O	
	Radio: BA_2_11.1.0.002_O	
	Application: BA_2_11.1.0.002_0	
	Middleware: BA_2_11.1.0.002_0	
	Firmware: 7.35.205.8_20190822	
NFC	NFC_NCIHALx_AR003C.8.3.0_O_OpnSrc	
PTT	3.1.39	
Touch FW	TC70x/TC75x = 1.9-Stylus-1-0 & TC51/TC56 = 1.8-Stylus-2.0	
RxLogger	5.4.12.0	
Bluetooth Pairing Utility	3.14	
Zebra Data Service	3.5.0.1162	
Files	8.1.0	
Stage Now	3.3.1.2000	
Battery Swap	1.0	
User Guide	1.0	
Camera	2.0.002	
MSRN	2.01	
Zebra Volume Control (ZVC)	2.1.0.14	
Battery Manger	1.4.2	
ActiveEdge	2.5.16	
WorryFree WiFi Analyzer	WFW_BA_2_5.0.0.005_O	
Device Central	2.1.0.9	
Zebra Software License Manager	3.1.1	
Audio	0.8.0.0	
Acoustic Profiles	TC51: General: AO1.1 Cellular: N/A TC51HC: General: AO2.1 Cellular: N/A TC70x: General: BO1.1 Cellular: N/A TC56: General: AO3.1 Cellular: AO3.2 TC75x: General: BO2.1 Cellular: BO2.1 VC80x: General: EO1.1 Cellular: N/A	
	MC33x: General: DO3.1 Cellular: N/A	

OemInfo	1.0.1.1128	
Enterprise Keyboard (EKB)	2.1.1.3	
WebView	73.0.3683.90	
Diagnostic Tool	1.17.0.9	
RFID Module	MC3300R: PAAEES00-001-R03	
RFID Radio	MC3300R: 2.0.30.0	
Zebra RFID Mobile (Demo App)	MC3300R: 2.2.7.1	
RFID Manager Application	MC3300R: 2.0.10.1	
RFID System Service	MC3300R: 2.0.4.2	
Finger Print	Zebra/TC70x/TC70x:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
	Zebra/TC51/TC51:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
	Zebra/TC51/TC51HC:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
	Zebra/TC75x/TC75x:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
	Zebra/TC75x/TC75xDF:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
	Zebra/TC56/TC56:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
	Zebra/VC80x/VC80x:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
	Zebra/MC33/MC33:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
	Zebra/MC33/MC33C:8.1.0/02-13-15.00-ON-U19-	
	STD/112:user/release-keys	
Security Patch Level	October 01 2019	

1. CFE v19 Updates:

- CFE_ATLAS_02-13-15.00-ON-U19-STD.zip (NGMS)
- Android Security Patch Level: October 01, 2019.
 Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/
- 2. Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - WLAN Version FUSION_BA_2_11.1.0.002_O
 - a. Adds Wi-Fi channel 144 support.
 - b. SPR37768 Resolved an issue where CPU utilization caused the device to become hot.

- c. SPR36111 Resolved an issue wherein Wi-Fi connection drops and unable to recover till a reboot.
- d. SPR36302 Resolved an issue wherein the audio call drops after several minutes into the call.
- e. SPR36618 Fixed an issue in which the device disconnects from and reconnects to Wi-Fi network often in some environments.
- f. SPR37841 Fixed an issue wherein the client is not waking up on time to receive the buffered data from the network, resulting in delayed audio call.
- g. Resolved an issue wherein the device goes into a connect and disconnect loop when FT (802.11r) is configured incorrectly on some Wireless LAN controllers.
- h. Retry count for the Wi-Fi communication packets have been increased to work better in some noisy environments
- i. Fixed an issue in which the client sometimes does not notify the Access Point for power save, resulting in data loss.
- j. Resolved an issue wherein the client does not roam to a better Access Point even though the current Access Point is seen at low RSSI.
- WorryFree WiFi Analyzer Version WFW_BA_2_5.0.0.005_0
 - This release supports Save, Export and Clear of Offline Connection Analysis data.
 - This release supports Save, Export and Clear of Offline Coverage View data.
 - This release supports Traceroute tool, a diagnostic utility for displaying the route path and measuring transit delays of data / Ping packets in the network.
 - Adds more Information Elements in the Scan List.
 - Adds support for user to chose either Management Packets or All packets for Logging.
- 1. SPR37987 Resolved an issue wherein device was not waking up from suspend on pressing side SCAN keys.
- 2. SPR37737 Resolved an issue wherein device was not able to scan using Right Scan Button in Chrome app when multiple tabs are open.
- 3. SPR37534 Resolved downgrade failure issues from Oreo LifeGuard Update 14 to Nougat LifeGuard updates via UPL method.
- 4. SPR38099 Resolved an issue wherein device was not able to switch OFF/ON RFID module from RFID Manager.
- 5. SPR37745 Resolved an issue wherein factory reset device fails to pair with BT when discoverability is disabled.
- 6. Resolved potential memory leak issue by integrating latest RFID SDK for RFID Demo app.

2. CFE v18 Updates:

CFE_ATLAS_02-13-15.00-ON-U18-STD.zip (NGMS)

1. Android Security Patch Level: September 01, 2019.

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - DataWedge Version 7.3.26
 - MXMF Version 9.0.4.3
 - EMDK Version 7.3.21.2321
 - OSx Version QCT.81.8.8.3
 - k. SPR37601 Resolved an issue wherein locale en_IE and es_MX was not being set successfully.
 - Scanning Framework Version 22.0.6.2
 - a. SPR37201 Resolved an issue wherein Scan Hard Trigger stops working once Language Settings are modified.
 - 1. Resolved an issue wherein RFID connect failures is observed for RFID SDK apps due to RFIDWedge enabled in the background.

3. CFE v17 Updates:

- CFE_ATLAS_02-13-15.00-ON-U17-STD.zip (NGMS)
- 1. Android Security Patch Level: August 01, 2019.

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - Fusion Version FUSION_BA_2_11.0.1.026_O
 - Radio Version BA_2_11.0.0.019_0
 - SimulScan Version 4.0.5 & SimulScanEngin Version 3.0.1
 - a. General optimizations in barcode scanning and OCR algorithms.
 - b. Miscellaneous bug fixes associated with demo app and stability test improvements.
 - c. Alignment with other supported Android platforms.
- 3. SPR37638 Resolved an issue wherein the set passcode prompt would show up on every reboot when the device was configured with AW along with enforcing pin profile and AW Launcher installed.
- 4. Workstation cradle features/fixes (TC5X only):

- When the device is placed in workstation dock cradle, display resolution is automatically set to 1080x1920 with a density of 200dp.
- When the device is removed from workstation dock cradle, display resolution is automatically set to 720x1280 with a density of 320dp.
- Resolved an issue wherein if device reboot is performed on the Workstation cradle, headset icon will not disappear on status bar even after undocking the device from the cradle.

4. CFE v16 Updates:

- CFE_ATLAS_02-13-15.00-ON-U16-STD.zip (NGMS)
- 1. Android Security Patch Level: July 01, 2019.

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - DataWedge Version 7.3.22
 - a. SYMBOL_TRIGGER_6 virtual key can be mapped using KeyManagerCSP to any physical keys and the mapped physical keys can then be used to trigger RFIDWedge.
 - MXMF Version 9.0.3.1
 - a. SPR36768 Resolved an issue wherein EHS Hostname in title was not reflecting updated Hostname after device reboot.
 - EKB Version 2.1.1.3
 - a. SPR37353 Enabled remapping of the right-side emoji icon in the EKB, both left and right emoji icons will be remapped to same key.
 - EMDK Version 7.3.18.2318
 - OSx Version QCT.81.8.8.2
 - Zebra Data Service Version 3.5.0.1162
 - OemInfo Version 1.0.1.1128
- 3. SPR35991 Resolved an issue wherein when soft-keyboard is switched, sometimes scan data stops to transmit to apps.
- 4. SPR36946 Resolved an issue wherein System UI crashes whenever user tries to open settings related options on user screen in EHS.
- 5. SPR36967 Resolved an issue wherein downgrading LG patch will cause "Error Zebra Plugin Stopped" popup.
- 6. CHINA/Indonesia SKU Support LTE/4G network option/capability is disabled for China/Indonesia SKU's.

7. Added support for Force Rotation feature & USB Ethernet adapter for CRD-TC5X-1SWS-01 (TC5X Workstation Docking Cradle).

5. CFE v15 Updates:

- CFE_ATLAS_02-13-15.00-ON-U15-STD.zip (NGMS)
- 1. Android Security Patch Level: June 01, 2019.

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - DataWedge Version 7.3.21
 - a. SPR37060 Resolved an issue wherein Datawedge was not disabling the scanner upon resume during app transition from background to foreground causing intermittent scanning failures.
 - b. SPR37124 Resolved an issue wherein ADF rule with crunch spaces was removing last character from barcode data with space.
 - EMDK Version 7.3.17.2317
 - b. SPR36925: Resolved an issue wherein scanner was not available for second app when an ANR or crash occurred on the first app.
 - MXMF Version 9.0.2.9
 - a. SPR36994 Resolved MX initialization issue wherein EHS was calling MX before completion of MX initialization process.
 - EKB Version 2.1.1.2
 - Device Central Version 2.1.0.9
- 3. SPR 35943 Added WebView version 73.0.3683.
- 4. SPR36961 Fixed an issue wherein User installation of RFID apps does not persist on non-RFID devices after reboot.
- 5. SPR36897: Added dun type to Telstra-M2M APN.
- 6. SPR37175 Fixed an issue wherein Two apps can enable the same scanner without one app releasing it.
- 7. SPR36927 Resolved an issue wherein scanner was not available for any app when multiple apps enabled the scanner and any app among them disable the scanner when it moves to background.

6. CFE v14 Updates:

CFE ATLAS 02-13-15.00-ON-U14-STD.zip (NGMS)

1. Android Security Patch Level: May 01, 2019.

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - DataWedge Version 7.3.18
 - StageNow Version 3.3.1.2000
 - EMDK Version 7.3.14.2314
 - MXMF Version 9.0.2.4
 - DDT Version 1.17.0.9
 - EKB Version 2.1.1.0
 - OemConfig Version 9.0.1.0
 - Scanning Framework Version 22.0.6.1
 - a. DotCode Symbology support is added for SE4750, SE4850, SE4710 and Camera Scanning.
 - b. Digimarc barcode decoding support is added for Camera Scanning.
 - c. Support for new Symbologies named FebraBan and Gridmatrix is added.
 - d. Instant Data Reporting (MultiBarcode) feature support is added.
 - OSx Version QCT.81.8.7
- 3. SPR36170 Fixed an issue wherein ntp sync does not work when parameters are updated using Stagenow.
- 4. SPR36143 Resolved an issue wherein remapping of control modifier keys were not persisting across a reboot.

7. CFE v13 Updates:

CFE_ATLAS_02-13-15.00-ON-U13-STD.zip (NGMS)

Note: This CFE is **not** applicable for **MC3300 R** Devices

1. Android Security Patch Level: April 01, 2019.

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- 2. Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - PTT Version 3.1.39
 - Device Central Version 2.0.22.1
 - OSX Version QCT.81.8.6_4

a. SPR36117/36095 – Resolved an issue wherein the scanned data would not come to the Apps, Airplane menu item was missing in the Power key menu and Home and recent buttons were not functional.

8. CFE v12 Updates:

CFE_ATLAS_02-13-15.00-ON-U12-STD.zip (NGMS)

Note: This CFE is *not* applicable for TC56, TC75x and MC3300 R Devices

1. Android Security Patch Level: February 01, 2019.

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - WorryFree WiFi Analyzer Version 3.2.20
 - MX: 8.4.1.3
 - a. SPR35665 Resolved an issue wherein Google Keyboard settings was not persisting.
 - b. SPR35491/35856 Resolved an issue wherein Analytics Manager was throwing "Index out of bound error" when a StageNow Barcode is scanned.
 - c. SPR35928 Resolved an issue where Clock Manager CSP accepts timezone id in "/Etc" Olson format.
 - d. SPR35908 Resolved an issue wherein admin and user generated certificates could not be downloaded from external server.
 - e. SPR34771 Resolved synchronization issue while checking with accessmanager.
 - StageNow client: 3.2.1.0
 - OEMConfig: 8.4.0.1
 - Datawedge: 7.2.5
 - EKB: 2.0.1.9
 - a. SPR35603 Fixed an issue wherein Enterprise Keyboard was getting disappeared when external Keyboard was connected.
 - EMDK: 7.2.2.2202
 - DDT: 1.16.1.3
- 3. SPR36019 Resolved an issue wherein serial port control signals were not working as expected.

9. CFE v11 Updates:

CFE_ATLAS_02-13-15.00-ON-U11-STD.zip (NGMS)

Note: This CFE is *not* applicable for TC56, TC75x and MC3300 R Devices

1. Android Security Patch Level: December 01, 2018.

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- 2. Updated below mentioned components: For more detail please refer http://techdocs.zebra.com
 - WLAN Version FUSION BA 2 11 0.0.024 O
 - ZVC Version 2.1.0.14
 - OemInfo Version 1.0.0.1059

Installation Requirements

- ADB installed on the PC (including adb drivers)
- USB debugging turned ON (from Developer options)
- TC51/TC70x/VC80x/MC33x has at least:
 - o Version 02-13-15.00-ON-U01-STD
- TC56/TC75x at least:
 - Version 02-13-15.00-ON-U08-STD
- MC3300R has at least:
 - o Version 02-13-15.00-ON-U13-STD

Installation Instructions

CFE software update procedure:

The installation instructions assume you have ADB installed on your PC (the adb drivers etc..) and your device has developer options enabled and USB debugging ON. Instructions on HOW TO enable ADB is also captured in the user guide.

- 1. Connect the device to the PC using the USB data cable or through the cradle.
- 2. You may need to pull down the top menu and if you see "USB for charging", touch it and then change it to "File transfers".
- 3. Open Command Prompt, run "adb devices" and check if you can see the device's serial number... If yes, proceed... if not, you will need to get the PC set up with the proper drivers or install an External SD Card.
- 4. You may also get a pop up on your PC (Win 7) that you will be connected as a Portable Media Player... this can be ignored.

Download Image

- a) CFE_ATLAS_02-13-15.00-ON-U19-STD.zip listed above in content section
- 5. Entering Recovery Mode
 - a. Choice 1: In Command Prompt, type "adb reboot recovery" and click enter.
 - b. Choice 2:
 - TC5x/TC7x: Reset and hold PTT key
 - VC80x: Reboot the VC80x using the power button menu and when the screen goes black, hold the Power and + buttons
 - MC33x/MC3300r: Reboot the device while holding the Pistol Grip Trigger (GUN Device) or the Right Scan Trigger (BRICK Device)
 - When Zebra Technologies logo appears on the screen release the PTT Key/Buttons/Trigger
- 6. Your device will reboot and put you on the Android Recovery screen.
- 7. If applying update via sideload Method
 - a. Use the Volume + and to highlight, "Apply update from ADB" and press the Power key to select it for applying OS upgrade package
- 8. if applying update via External SD card
 - a. Use the Volume + and to highlight "Apply update from SD card" and press the Power Key to select it
 - b. Use the Volume + and to highlight package CFE_ATLAS_02-13-15.00-ON-U19-STD.zip and press the Power Key to select it.
 - c. Go to Step 10 once above steps are completed
- 9. With your Command Prompt open in the Host machine, type "adb sideload" command and add a space and then drag and drop the CFE_ATLAS_02-13-15.00-ON-U19-STD.zip file on to it and click enter.
 - a. Your PC screen will show files being installed and a little blue horizontal progress bar on your device will show status... and after about 6~ minutes (could be 10+ minutes if installing GMS) it should be done and you should be back at the Android Recovery screen.
- 10. "Reboot system now" is highlighted. Press the Power Key to Reboot.
- 11. At the Home Screen, we need to verify that the BSP upgrade took place and set the Date & Time.
 - a. Go to "Settings" and scroll down to "About phone" and look at the "Build number". It should start with "02-13-15.00-ON-U19-STD release keys". Now you are on the correct BSP.
- 12. Now you are all set to use your Zebra Device.

Device Compatibility

This software release has been approved for use on the following devices.

TC51		
Device Part Number	Operating System	
TC510K-1PAZU2P-US	Android M, N, O	
TC510K-1PAZU2P-A6	Android M, N, O	
TC510K-1PAZU4P-US	Android M, N, O	
TC510K-1PAZU4P-A6	Android M, N, O	
TC510K-1HDZU2P-US	Android M, N, O	
TC510K-1HDZU4P-US	Android M, N, O	
TC510K-1HDZU2P-A6	Android M, N, O	
TC510K-1HDZU4P-A6	Android M, N, O	
TC510K-1PAZU2P-IA	Android M, N, O	
TC510K-1PAZU4P-IA	Android M, N, O	

TC70x		
Device Part Number		
TC700K-02B22B0-A6	Android M, N, O	
TC700K-02B24B0-A6	Android M, N, O	
TC700K-02B22B0-US	Android M, N, O	
TC700K-02B24B0-US	Android M, N, O	
TC700K-02B22B0-IA	Android M, N, O	

Supported FIPS and TAA Compliant SKUS:

FIPS and TAA Compliant SKUS		
Device Part Number	Operating System	
TC510K-1PAZU4P-FT	Android M, N, O	
TC510K-1HDZU4P-FT	Android M, N, O	
TC700K-02B24B0-FT	Android M, N, O	

TC56		
Device Part Number	Operating System	
TC56CJ-2PAZU2P-US	Android M, N, O	
TC56CJ-2PAZU2P-A6	Android M, N, O	
TC56DJ-2PAZU2P-A6	Android M, N, O	
TC56DJ-2PAZU2P-BR	Android M, N, O	
TC56DJ-2PAZU2P-IA	Android M, N, O	

TC56DJ-2PAZU2P-CN	Android M, N, O
TC56DJ-2PAZU2P-TN	Android M, N, O
TC56DJ-2PAZU2P-ID	Android M, N, O
TC56CJ-2PAZU4P-US	Android M, N, O
TC56CJ-2PAZU4P-A6	Android M, N, O
TC56DJ-2PAZU4P-A6	Android M, N, O
TC56DJ-2PAZU4P-BR	Android M, N, O
TC56DJ-2PAZU4P-IA	Android M, N, O
TC56DJ-2PAZU4P-CN	Android M, N, O
TC56DJ-2PAZU4P-TN	Android M, N, O
TC56DJ-2PAZU4P-ID	Android M, N, O

ТС75х		
Device Part Number	Operating System	
TC75EK-22B22AB-US	Android M, N, O	
TC75EK-22B24AB-US	Android M, N, O	
TC75EK-22F22AB-US	Android M, N, O	
TC75EK-22B22AF-US	Android M, N, O	
TC75FK-22B22AD-A6	Android M, N, O	
TC75FK-22B24AD-A6	Android M, N, O	
TC75FK-22B22AD-BR	Android M, N, O	
TC75FK-22B22AD-IA	Android M, N, O	
TC75FK-22B22AD-ID	Android M, N, O	
TC75FK-22B22AD-TN	Android M, N, O	
TC75FK-22F22AD-A6	Android M, N, O	
TC75FK-22B22AD-TW	Android M, N, O	
TC75GK-22B22AD-A6	Android M, N, O	
TC75GK-22B24AD-A6	Android M, N, O	
TC75GK-22F22AD-A6	Android M, N, O	

Supported FIPS and TAA Compliant SKUS:

FIPS and TAA Compliant SKUS		
Device Part Number		
TC56CJ-2PAZU4P-FT		

FIPS and TAA Compliant SKUS

Device Part Number

VC	80x USA	
	Device Part Number	Operating System
Warehouse AOSP	VC80X-10SSRAABBA-U	Android N, O
Freezer AOSP	VC80X-10FSRAABBA-U	Android N, O
Outdoor AOSP	VC80X-10SORAABBA-U	Android N, O
	•	
VC80x Re	st of the World	
Warehouse AOSP	VC80X-10SSRAABBA-I	Android N, O
Freezer AOSP	VC80X-10FSRAABBA-I	Android N, O
Outdoor AOSP	VC80X-10SORAABBA-I	Android N, O
VC	30x India	
Warehouse AOSP India	VC80X-10SSRAABBA-IN	Android N, O
Outdoor AOSP India	VC80X-10SORAABBA-IN	Android N, O

MC33x	
Device Part Number	Operating System
MC330K-GE3HA3NA	Android N, O
MC330K-GE3HA3RW	Android N, O
MC330K-GE4HA3NA	Android N, O
MC330K-GE4HA3RW	Android N, O
MC330K-GE4HA4NA	Android N, O
MC330K-GE4HA4RW	Android N, O
MC330K-GI3HA3NA	Android N, O
MC330K-GI3HA3RW	Android N, O
MC330K-GI3HA4RW	Android N, O
MC330K-GI4HA3NA	Android N, O
MC330K-GI4HA3RW	Android N, O
MC330K-GI4HA4NA	Android N, O
MC330K-GI4HA4RW	Android N, O
MC330K-GI4HG3NA	Android N, O
MC330K-GI4HG3RW	Android N, O
MC330K-GI4HG4NA	Android N, O
MC330K-GI4HG4RW	Android N, O
MC330K-GL2HA3RW	Android N, O
MC330K-GL3HA3RW	Android N, O
MC330K-GL3HA4RW	Android N, O
MC330K-GL4HA3NA	Android N, O
MC330K-GL4HA3RW	Android N, O

МС33х	
Device Part number	Operating System
MC330M-RL4SG2RW	Android N, O
MC330M-SI2HA2RW	Android N, O
MC330M-SI30A2RW	Android N, O
MC330M-SI3HA2NA	Android N, O
MC330M-SI3HA2RW	Android N, O
MC330M-SI40A2NA	Android N, O
MC330M-SI4HA2NA	Android N, O
MC330M-SI4HA2RW	Android N, O
MC330M-SI4HG2NA	Android N, O
MC330M-SL2HA2RW	Android N, O
MC330M-SL2HG2RW	Android N, O
MC330M-SL3HA2NA	Android N, O
MC330M-SL3HA2RW	Android N, O
MC330M-SL4HA2NA	Android N, O
MC330M-SN3HA2RW	Android N, O
MC330M-SN4HA2NA	Android N, O
MC330M-RL2SG2US	Android N, O
MC330M-SL4HG2US	Android N, O
MC330M-SL3HG2US	Android N, O
MC330M-RL4SG2US	Android N, O
MC330M-RL3HG2US	Android N, O
MC330M-SN4HG2US	Android N, O

MC330K-GL4HA4NA	Android N, O
MC330K-GL4HA4RW	Android N, O
MC330K-GL4HG3RW	Android N, O
MC330K-RC3HA4NA	Android N, O
MC330K-RC3HA4RW	Android N, O
MC330K-RC3HG4RW	Android N, O
MC330K-RC4HA4NA	Android N, O
MC330K-RC4HA4RW	Android N, O
MC330K-RL3HA3RW	Android N, O
MC330K-RL3HG3RW	Android N, O
MC330K-RL3SG3RW	Android N, O
MC330K-RL4HA3NA	Android N, O
MC330K-RL4HA3RW	Android N, O
MC330K-RL4HG3NA	Android N, O
MC330K-SB3HA4NA	Android N, O
MC330K-SB3HA4RW	Android N, O
MC330K-SB3HG4RW	Android N, O
MC330K-SB4HA4NA	Android N, O
MC330K-SB4HA4RW	Android N, O
MC330K-SB4HG4NA	Android N, O
MC330K-SE2HA3RW	Android N, O
MC330K-SE3HA3NA	Android N, O
MC330K-SE3HA3RW	Android N, O
MC330K-SE4HA3NA	Android N, O
MC330K-SE4HA3RW	Android N, O
MC330K-SG3HA4NA	Android N, O
MC330K-SG3HA4RW	Android N, O
MC330K-SG4HA4NA	Android N, O
MC330K-SI2HA3RW	Android N, O
MC330K-SI3HA3NA	Android N, O
MC330K-SI3HA3RW	Android N, O
MC330K-SI3HG3RW	Android N, O
MC330K-SI4HA3NA	Android N, O
MC330K-SI4HA3RW	Android N, O
MC330K-SI4HG3NA	Android N, O
MC330K-SL2HA3RW	Android N, O
MC330K-SL4HA3RW	Android N, O
MC330K-SN3HA3RW	Android N, O
MC330K-SN4HA3NA	Android N, O
MC330K-SN4HA3RW	Android N, O
MC330K-SP3HA4NA	Android N, O

MC330M-SI3HG2US	Android N, O
MC330M-GL4HG2US	Android N, O
MC330M-GL3HG2US	Android N, O
MC330M-GL2HG2US	Android N, O
MC330M-GI3HG2US	Android N, O
MC330M-GI2HG2US	Android N, O
MC330K-SN4HG3US	Android N, O
MC330K-SI3HG3US	Android N, O
MC330K-GL4HG3US	Android N, O
MC330K-RC4HG4US	Android N, O
MC330K-RC3HG4US	Android N, O
MC330K-GL4HG4US	Android N, O
MC330K-GI3HG3US	Android N, O
MC330K-SP4HG4US	Android N, O
MC330K-SP3HG4US	Android N, O
MC330K-SB3HG4US	Android N, O
MC330K-SE4HG3US	Android N, O
MC330K-SE3HG3US	Android N, O
MC330K-SE2HG3US	Android N, O
MC330K-GE4HG3US	Android N, O
MC330K-GE3HG3US	Android N, O
MC330K-GE2HG3US	Android N, O
MC330K-SG4HG4US	Android N, O
MC330K-SG3HG4US	Android N, O
MC330K-SG2HG4US	Android N, O
MC330K-GE4HG4US	Android N, O
MC330K-GE2HG4US	Android N, O
MC330K- GI3HG3US01	Android N, O
MC330M-SN3HG2RW	Android N, O
MC330M-SL3HG2RW	Android N, O
MC330M-SI4HG2RW	Android N, O
MC330M-SI3HG2RW	Android N, O
MC330M-SI2HG2RW	Android N, O
MC330M-RL3HG2RW	Android N, O
MC330M-RL2SG2RW	Android N, O
MC330M-GL4HG2RW	Android N, O
MC330M-GL2HG2RW	Android N, O
MC330M-GI4HG2RW	Android N, O
MC330M-GI4HG2IN	Android N, O
MC330M-GI3HG2IN	Android N, O
MC330M-GI2HG2RW	Android N, O
	, -

MC330K-SP3HA4RW	Android N, O
MC330K-SP4HA4NA	Android N, O
MC330K-SP4HA4RW	Android N, O
MC330M-GI2HA2NA	Android N, O
MC330M-GI2HA2RW	Android N, O
MC330M-GI30A2RW	Android N, O
MC330M-GI3HA2IN	Android N, O
MC330M-GI3HA2NA	Android N, O
MC330M-GI3HA2RW	Android N, O
MC330M-GI3HG2RW	Android N, O
MC330M-GI40A2NA	Android N, O
MC330M-GI4HA2IN	Android N, O
MC330M-GI4HA2NA	Android N, O
MC330M-GI4HA2RW	Android N, O
MC330M-GI4HG2NA	Android N, O
MC330M-GL2HA2NA	Android N, O
MC330M-GL2HA2RW	Android N, O
MC330M-GL3HA2NA	Android N, O
MC330M-GL3HA2RW	Android N, O
MC330M-GL3HG2RW	Android N, O
MC330M-GL40A2NA	Android N, O
MC330M-GL40A2RW	Android N, O
MC330M-GL4HA2NA	Android N, O
MC330M-GL4HA2RW	Android N, O
MC330M-RL2SA2NA	Android N, O
MC330M-RL2SA2RW	Android N, O
MC330M-RL3HA2NA	Android N, O
MC330M-RL3HA2RW	Android N, O
MC330M-RL3SA2NA	Android N, O
MC330M-RL3SA2RW	Android N, O
MC330M-RL3SG2NA	Android N, O
MC330M-RL3SG2RW	Android N, O
MC330M-RL40A2NA	Android N, O
MC330M-RL4SA2NA	Android N, O
MC330M-RL4SA2RW	Android N, O

MC330K-SP4HG4RW	Android N, O
MC330K-SP3HG4RW	Android N, O
MC330K-SN4HG3RW	Android N, O
MC330K-SN3HG3RW	Android N, O
MC330K-SL4HG3RW	Android N, O
MC330K-SL2HG3RW	Android N, O
MC330K-SI4HG3RW	Android N, O
MC330K-SI2HG3RW	Android N, O
MC330K-SG3HG4RW	Android N, O
MC330K-SG2HG4RW	Android N, O
MC330K-SE4HG3RW	Android N, O
MC330K-SE3HG3RW	Android N, O
MC330K-SE2HG3RW	Android N, O
MC330K-SB4HG4RW	Android N, O
MC330K-RL4HG3RW	Android N, O
MC330K-RC4HG4RW	Android N, O
MC330K-GL4HG3RW	Android N, O
MC330K-GL3HG4RW	Android N, O
MC330K-GL3HG3RW	Android N, O
MC330K-GL2HG3RW	Android N, O
MC330K-GI3HG4RW	Android N, O
MC330K-GI3HG3RW	Android N, O
MC330K-GE4HG4RW	Android N, O
MC330K-GE4HG3RW	Android N, O
MC330K-GE3HG3RW	Android N, O
MC330K-GE2HG4RW	Android N, O
MC330K-GE2HG3RW	Android N, O
MC330K- GI3HG3RW01	Android N, O
MC330K-GE2HA3US	Android N, O
MC330K-GE2HA4US	Android N, O
MC330K-SE2HA3US	Android N, O
MC330K-SG2HA4US	Android N, O
MC330K-GE2HA3RW	Android N, O
MC330K-GE2HA4RW	Android N, O
MC330K-SG2HA4RW	Android N, O

MC3300R MC3300R

Device Part Number	Operating System
MC333R-GI2HA4IL	Android N, O
MC333R-GI2HA4CN	Android N, O
MC333R-GI4HA4CN	Android N, O
MC339R-GF4HA4CN	Android N, O

Device Part Number	Operating System
MC339R-GE2HA4CN	Android N, O
MC339R-GF2HA4CN	Android N, O
MC339R-GE4HA4CN	Android N, O

Known Issues and Limitations

- 1. USB audio headset is not supported on Workstation Cradle.
- 2. For an existing Data wedge profile which is configured for Image barcode scanning, if the user updates the profile for SimulScan data capture and reboots the device, the decoder list is shown as blank under DataWedge settings. As a workaround, user needs to use two different Data wedge profiles one for Imager barcode scanning and other profile for Simul scan data capture.
- 3. Velocity application stops if user use the Android Recent button to close Velocity app. As a workaround, user can close the application from the velocity application client menu.
- 4. Ethernet shows Connected state when device is configured with Static IP and placed in multislot cradle without Ethernet cable.

Last Revised: <05-14-2020>