

---

# Release Notes – DATAWEDGE TOOLKIT v03.07.22 - Hotfix CFE Package

---

[Introduction](#)

[Description](#)

[Package Details](#)

[Device Compatibility](#)

[Installation Requirements](#)

[Installation Instructions](#)

[Release Date](#)

## Introduction

---

Hotfix CFE (Cumulative Fixes from Engineering) Package contains multiple SPR Hotfixes into a single package. The Hotfix CFE Package helps the end users to keep up to date with all the SPR hotfixes for given product software release / revision.

Hotfix CFE packages are validated only by engineering validation team and the package follows Zebra Technologies Hotfix Package Policy. Click here to view [Hotfix Package Policy](#).

## Description

---

CFE package DataWedgev030722.CAB file includes the following Hotfixes:

SPR No	Synopsis
36346	Deficient scanner performance overserved while decoding damaged I2OF5 barcode

This Hotfix CFE package DataWedgev030722.CAB obsoletes the following Hotfix CFEs:

Hotfix CFE version
DataWedgev030720.CAB

*Note: Latest CFE package includes previous hotfix package hotfixes and new SPR hotfix.*

Please refer <https://www.zebra.com/us/en/support-downloads/software/utilities/datawedge-toolkit.html> for fixes / improvement in all older DataWedge releases.

## Package Details

---

DataWedgev030722.cab

## Device Compatibility

---

This Hotfix CFE Package software release has been approved for use with the following Zebra devices.

Device	Operating System
MC32N0	CE 7.0
WT41N0	CE 7.0
MC92N0	CE 7.0
MC92N0	WM 6.5
MC18N0	CE7.0
MC67NA Premium	WM 6.5
MC67NA Base	WM 6.5
MC67ND	WM 6.5
MC55E0	WM 6.5
VC70	CE 7.0
MC2100	CE 6.0
MC31	WM 6.5
MC31	CE 6.0
MC55A0	WM 6.5
MC55N0	WM 6.5
MC9190	CE 6.0

MC9190	WM 6.5
MC95	WM 6.5

## Installation Requirements

---

The Hotfix CFE cab can be deployed to the Mobile device through any one of the below mentioned methods. For installing the cab, the users should have at least one of the below mentioned tools.

- Windows Mobile Device Center (For Windows Desktops)
- SD Cards / Micro SD cards
- MDM set up

## Installation Instructions

---

### For Normal installation of the PATCH:

- **Windows Mobile Device Center (For Windows Desktops) Installation Instructions:**
  1. Copy "DataWedgev030722.CAB" file to the Application folder on the device.
  2. Deploy the solution by tapping on the "DataWedgev030722.CAB" file.
- **SD Cards / Micro SD cards Installation Instructions:**
  1. Copy "DataWedgev030722.CAB" file to the SD card.
  2. Deploy the solution by tapping on the "DataWedgev030722.CAB".

### For MSP or REMOTE installation of the PATCH:

1. Set up MDM (MSP, Soti, Airwatch, etc..) to send "DataWedgev030722.CAB" file to the application folder of the device.
2. To deploy the solution, setup in MDM to install the cab file "DataWedgev030722.CAB" file.

## Release Date

---

Feb 2019