



Zebra MiniScan MS954 Series

Fixed Mount Scanner

Compact, durable and high performance fixed-mount bar code scanner

The MS954 is a compact, durable, fixed-mount laser bar code scanner for premium linear scanning on all types of 1-D bar codes, including poorly printed and low contrast symbols.

The MS954 offers a configurable scan angle of 47° and 35° for OEM devices requiring a flexible, expanded working range. As one of the smallest, lightest and brightest fixed-mount scanners available today, the MS954 is ideal for accurate automated data collection in OEM device designs with space constraints. It can also be used as a standalone fixed-mount scanner.

Rich feature set for more flexibility in many environments

The MS954 features a configurable scan angle and a working range of over 35 inches/88.9 cm to ensure high first-time read rates for maximum productivity. The MS954 is easy to programme and configure, enabling you to cut your development time and bring your product to market faster — even if you don't have the in-house technical resources for scanner integration. With its durable housing and built-in RS-232 interface, the MS954 enables your project teams to quickly and confidently integrate high performance 1-D bar code data capture into many applications.

Proven technology to enhance your solutions

With millions of installations worldwide, our OEM devices are proven to deliver high reliability and superior performance, ensuring the accurate and quick capture of data and images in your mission-critical applications and devices. In addition, an easy-to-integrate design and expert assistance from our world-class OEM support team enable you to bring your systems to market quickly and cost effectively. And since even the most intelligent products require a maintenance plan and a support strategy, we offer superior services to help you maximize uptime and maintain peak performance.

For more information on the MS954, access our global contact directory at www.zebra.com/contact or visit us on the web at www.zebra.com/ms954

MS954 Specification Highlights

PHYSICAL CHARACTERISTICS

Dimensions: 1.02H x 1.93W x 2.31D (in) 25.9H x 49.02W x 58.67D (mm)

Weight: 1.67 oz./ 47.34 g

Interface: RS-232

PERFORMANCE CHARACTERISTICS

Light source: Visible laser diode 650 nm

Scan rate: 104 ± 12 scans per second

Scan angle: 47° ± 3° (typical) / 35° ± 3° (narrow)

Scan pattern: Linear

FEATURES

High performance fixed-mount scanner

Premium scanning on poorly printed and low contrast 1-D symbols for maximum accuracy and productivity

Working range from near contact to over 35 in./88.9 cm

Flexible decode range for maximum accuracy and efficiency

Configurable scan angle of 47° and 35°

Ability to control scan angle to meet demands of application

Compact durable housing, mounting holes, LEDs and RS-232 interface

Plug-and-play installation reduces development time and speeds up time to market

Software controlled or manual triggering

Offers flexible control for unattended or hands-free applications

Easy-to-programme simple serial interface (SSI)

Provides fast, simple communications between scanner and host

Reads all major 1-D symbologies

Versatile decode capability enables devices to realize a high first-time read rate for improved productivity

USER ENVIRONMENT

Ambient lighting tolerance: Tolerant to typical artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED1: 450 Ft Candles (4,844 Lux) Sunlight: 8000 Ft Candles (86,111 Lux)

Operating temperature: -4° to 140°F (-20° to 60°C)

Storage temperature : -40° to 158°F (-40° to 70°C)

Humidity: 5% to 95% non-condensing

Power: Input voltage: 5 VDC ± 10%
Scanning current: 95mA Standby
current: 27mA Vcc noise level:
200mV peak-to-peak max

Drop Rating: Unit functions normally after multiple 30 in (76 cm) drops to concrete

Symbologies: All major 1-D bar codes

Programmable parameters: Laser On Time, Aim Duration, Power Mode, Trigger Mode, Bi-directional Redundancy, Symbology Types/Lengths, Data Formatting, Serial Parameters, Beeper Tone, Scan Angle

Minimum print contrast: Minimum 25% absolute dark/light reflectance measured at 650 nm

Ranges - 1-D codes: **5 mil:** Code 39; 2.5:1 - 0.7 - 7.3 (in) / 1.8 - 18.54 (cm) **7.5 mil:** Code 39; 2.5:1 - 0.9 - 12.4 (in) / 2.29 - 31.24 (cm) **13 mil:** 100% UPC - 80%MRD: 0.9 - 22 (in) / 2.29 - 55.88 (cm) **20 mil:** Code 39; 2.2:1 - * - 27.5 (in) / * - 69.85 (cm) **20 mil:** Code 39; 2.2:1 - 80% MRD: 2 - 30 (in) / 5.08 - 76.2 (cm) **40 mil:** Code 39; 2.2:1 - * - 28 (in) / * - 71.12 (cm) **55 mil:** Code 39; 2.2:1 - * - 35 (in) / * - 88.90 (cm)

* = Near ranges on lower densities (not specified) largely depend on the width of the bar code and the scan angle.
1 - LED lighting with high AC ripple content can impact scanning performance

Bright 650 nm laser diode

Scan line is easy to see

Software developer's kit (SDK) at no extra charge

Enables the creation of applications using familiar Microsoft® Windows® 98, 2000 and XP platforms

Applications

OEM embedded

Kiosks and ATMs; clinical diagnostics; medical instruments; blood and chemical analysis; gaming equipment; vending and lottery machines; turnstiles/ access control

Fixed-mount

Manufacturing and warehousing; assembly lines ; library and document tracking

REGULATORY

Laser classification: CDRH Class II, IEC Class 2

Electrical safety: Certified to UL1950, CA C22-2 NO950 ENG60950/ IEC950

Environmental: RoHS compliant

EMI/RFI: FCC Part 15 Class B, ICES-003 Class B European Union ENC Directive, Australian SMAV



ZEBRA

Part number PSS-MS954-A. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES