



MC9200 OPERATING SYSTEM BSP 13.54.02 - HOTFIX CFE 01.00.00 RELEASE NOTES

INTRODUCTION

SPR 27865 reported an issue wherein the MC92 device does not pair with RS507 when using Telnet Client.

DESCRIPTION

The provided fix resolves the MC92 pairing issue with RS507 using Telnet Client.

Note: This fix works with latest Telnet client **WLTE_MOT_MC92N0_WM65_7_3_196_AS.exe**. This Telnet version is available to download from www.wavelink.com.

CONTENTS

SPR27865_MC92_W65_en_135402_v1_0_WB.cab (HotFix package with Warm boot)

SPR27865_MC92_W65_en_135402_v1_0_NB.cab (HotFix package without Warm boot)

DEVICE COMPATIBILITY

This HotFix CFE Package software release has been approved for use with the following Zebra devices.

Device	Operating System	BSP Version
MC92N0 Premium	WM 6.5	v13.54.02

INSTALLATION REQUIREMENTS

The HotFix cab can be deployed to the Mobile device through any one of the below mentioned methods. For installing the cab, the users should have at least one of the below mentioned tools.

- Windows Mobile Device Center (For Windows Desktops)
- SD Cards / Micro SD cards
- MDM Set up

INSTALLATION INSTRUCTIONS

For Normal installation of the PATCH:



- Windows Mobile Device Center (For Windows Desktops) Installation Instructions:

1. Copy "SPR27865_MC92_W65_en_135402_v1_0_WB.cab" file to the Application folder on the device.

2. Deploy the solution by tapping on the "SPR27865_MC92_W65_en_135402_v1_0_WB.cab" file.

3. After successful deployment of the "SPR27865_MC92_W65_en_135402_v1_0_WB.cab" file device will do an automatic warm boot.

- SD Cards / Micro SD cards Installation Instructions:

1. Copy "SPR27865_MC92_W65_en_135402_v1_0_WB.cab" file to the SD card.

2. Deploy the solution by tapping on the "SPR27865_MC92_W65_en_135402_v1_0_WB.cab"

3. After successful deployment of the "SPR27865_MC92_W65_en_135402_v1_0_WB.cab" file device will do an automatic warm boot.

For MSP or REMOTE installation of the PATCH:

1. Set up MDM (MSP, Soti, Airwatch, etc..) to send "SPR27865_MC92_W65_en_135402_v1_0_NB.cab" file to the application folder of the device.

2. To deploy the solution, setup in MDM to install the cab file "SPR27865_MC92_W65_en_135402_v1_0_NB.cab" file.

3. Changes will take effect after a manual reboot of the terminal or if MDM reboots device.

RELEASE DATE

September 2015