

WT41N0 CE 7.0 - BSP V04.57.05 -HOTFIX CFE V02.08.00 PACKAGE RELEASE NOTES

INTRODUCTION

HotFix CFE (Cumulative Fixes from Engineering) Package contains multiple SPR Hotfixes into a single package. The HotFix CFE Package helps the end users to keep up to date with all the SPR hotfixes for given product software release / revision.

HotFix CFE packages are validated only by engineering validation team and the package follows Zebra Technologies HotFix Package Policy.

Hotfix Support Policy

DESCRIPTION

CFE package CFE_WT41_CE_045705_EN_v020800_e_WB.cab / CFE_WT41_CE_045705_EN_v020800_e_NB.cab file includes the following HotFixes:

SPR No	Synopsis
31278	Stylus right click and double click in Remote Desktop doesn't work
30676	When opening a Multi-File Playlist in windows Media Player, first file is opened and played and when next file is attempted to be opened / played Windows Media Player closes/disappears
29193	Audio dropout when using Bluetooth Audio (WBA) headset
30621	Audio gets fail while text to speech application is running on the device
30384	Does not disable an illumination on RS507 through corded adapter or



	bluetooth when connected to the device.
30742	Sometimes the audio is not routed BT Headset or audio is not recorded through microphone when HS3000 BT Headset connected/disconnected several times manually
28945	Can't add Printer to Remote Desktop Client.
27756	Device is Crashing/Freezing inside the cradle at times. Recovery is via a cold boot only.

This HotFix CFE package

CFE_WT41_CE_045705_EN_v020800_e_WB.cab/CFE_WT41_CE_045705_EN_v 020800_e_NB.cab obsoletes the following HotFix CFEs:

HotFix CFE version

CFE_WT41_CE_045705_EN_v010401_e_NB.cab CFE_WT41_CE_045705_EN_v010401_e_WB.cab

Note: Latest CFE package includes previous CFE package hot fixes and new SPR hot fix.

CONTENTS

CFE_WT41_CE_045705_EN_v020800_e_WB.cab (CFE package with auto Warm boot)

CFE_WT41_CE_045705_EN_v020800_e_NB.cab (CFE package without auto Warm boot)

DEVICE COMPATIBILITY

This HotFix CFE Package software release has been approved for use with the following Zebra devices.



Device	Operating System	BSP Version
WT41N0	CE 7.0	v04.57.04/v04.57.05

INSTALLATION REQUIREMENTS

The HotFix CFE cab can be deployed to the Mobile device through any one of the below mentioned methods. For installing the cab, the users should have at least one of the below mentioned tools.

- Windows Mobile Device Center (For Windows Desktops)
- SD Cards / Micro SD cards
- MDM set up

INSTALLATION INSTRUCTIONS

For Normal installation of the PATCH:

• Windows Mobile Device Center (For Windows Desktops) Installation Instructions:

1. Copy "CFE_WT41_CE_045705_EN_v020800_e_WB.cab" file to the Application folder on the device.

2. Deploy the solution by tapping on the "CFE_WT41_CE_045705_EN_v020800_e_WB.cab" file.

3. After successful deployment of the "CFE_WT41_CE_045705_EN_v020800_e_WB.cab" file, device will do an automatic warm boot.

• SD Cards / Micro SD cards Installation Instructions:

1. Copy "CFE_WT41_CE_045705_EN_v020800_e_WB.cab" file to the SD card.

2. Deploy the solution by tapping on the "CFE_WT41_CE_045705_EN_v020800_e_WB.cab".

3. After successful deployment of the "CFE_WT41_CE_045705_EN_v020800_e_WB.cab" file, device will do an automatic warm boot.

For MSP or REMOTE installation of the PATCH:



1. Set up MDM (MSP, Soti, Airwatch, etc..) to send "CFE_WT41_CE_045705_EN_v020800_e_NB.cab" file to the application folder of the device.

2. To deploy the solution, setup in MDM to install the cab file "CFE_WT41_CE_045705_EN_v020800_e_NB.cab" file.

3. Changes will take effect after a manual reboot of the terminal or if MDM reboots device.

RELEASE DATE

February, 2017