



# Z-Ultimate 4000T 8.0 mil Tag

## FEATURES

- Thermal transfer, gloss polyester laminated 8.0 mil tag
- Excellent smear/scratch resistance
- Excellent durability and chemical resistance
- Topcoating is suitable for fanfolding
- Available in white (05470RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White, polyester/ polypropylene lamination	8.0 mil
TOTAL ± 10%		8.0 mil

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
N/A	-40° F to 200° F (-40° C to 93° C)	72° F (22° C) at 50% RH

**Expected Exterior Life**  
2 years

## CHEMICAL RESISTANCE

Chemical		Suggested Ribbon	
		6200	5100
Weak	Blood	●	●
	Body Fluid	●	●
	Salt Water	●	●
	Water	●	●
	Window Cleaner	●	●
Moderate	Alcohol	●	●
	Ammonia	●	●
	Bleach	●	●
	IPA	●	●
Harsh	Gasoline	●	●
	Grease	●	●
	Oil	●	●
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

- Outdoor storage tags



- High-strength hang tags



- Water-immersed tags



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)